

Issuing Date 21-Sep-2012

Revision Date 26-Dec-2012

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Mothers Professional Rubbing Compound

Product Code(s) 08612, 38612

Recommended Use Car care

Supplier Address

MOTHERS POLISHES WAXES CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

May cause skin and eye irritation
Harmful: may cause lung damage if swallowed

Appearance White.

Physical State Liquid.

Odor Naphthalenic

Potential Health Effects

Principle Routes of Exposure Skin contact. Eye contact.

Acute Toxicity

Eyes

May cause irritation.

Skin

May cause irritation. Repeated exposure may cause skin dryness or cracking.

Inhalation

May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Ingestion

Harmful: may cause lung damage if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects

Repeated contact may cause allergic reactions in very susceptible persons.

Aggravated Medical Conditions

Pre-existing eye disorders. Skin disorders. Respiratory disorders.

Environmental Hazard

See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	10-25
Aluminum oxide	1344-28-1	< 15
Paraffinic, naphthenic solvent	64742-47-8	< 10
Glycerol	56-81-5	< 10
Aluminum nitrate nonahydrate	7784-27-2	< 10
White mineral oil	8042-47-5	< 10
Paraffin oils	8012-95-1	< 10
Calcined kaolin clay	66402-68-4	< 1
Isopropyl alcohol	67-63-0	0.1-1

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
Inhalation	Move to fresh air.
Ingestion	Clean mouth with water and afterwards drink plenty of water.
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Not flammable.			
Flash Point	> 221.3 °F / > 105 °C			
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Explosion Data				
Sensitivity to Mechanical Impact	None.			
Sensitivity to Static Discharge	None.			
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
NFPA	Health Hazard 1	Flammability 0	Instability 0	Physical and Chemical Hazards N/A
HMIS	Health Hazard 1*	Flammability 0	Physical Hazard 0	Personal Protection B

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with eyes.
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8.
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material. Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes.

Storage Keep containers tightly closed in a cool, well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum oxide 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	
Glycerol 56-81-5	-	TWA: 15 mg/m ³ mist, total particulate TWA: 5 mg/m ³ mist, respirable fraction (vacated) TWA: 10 mg/m ³ mist, total particulate (vacated) TWA: 5 mg/m ³ mist, respirable fraction	
Aluminum nitrate nonahydrate 7784-27-2	-	(vacated) TWA: 2 mg/m ³ Al Aluminum	TWA: 2 mg/m ³ Al
Calcined kaolin clay 66402-68-4	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr TWA: 0.2 mg/m ³ Mn	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust
Paraffin oils 8012-95-1	TWA: 5 mg/m ³ inhalable fraction excluding metal working fluids, highly & severely refined	-	
White mineral oil 8042-47-5	TWA: 5 mg/m ³ inhalable fraction excluding metal working fluids, highly & severely refined	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³	IDLH: 2500 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³

Engineering Measures Showers
Eyewash stations
Ventilation systems

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin and Body Protection

Protective gloves.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White.	Odor	Naphthalenic.
Odor Threshold	No information available.	Physical State	Liquid.
pH	8.1	Autoignition Temperature	No information available.
Flash Point	> 221.3 °F / > 105 °C	Boiling Point/Boiling Range	114 °C
Decomposition Temperature	No information available.	Flammability Limits in Air	No information available.
Melting Point/Range	No information available.		
Specific Gravity	1.021	Solubility	No information available.
Evaporation Rate	No information available.	Vapor Pressure	No data available.
Vapor Density	No data available.	Viscosity	8500-9500 cps

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	None known based on information supplied.
Conditions to Avoid	Heat, flames and sparks.
Hazardous Decomposition Products	None known based on information supplied.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

Inhalation	No known effect. Avoid breathing vapors or mists.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	Prolonged contact may cause redness and irritation.
Ingestion	No known effect.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Aluminum oxide	> 5000 mg/kg (Rat)		
Paraffinic, naphthenic solvent	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Glycerol	= 12600 mg/kg (Rat)	21900 mg/kg (Rat)	
Aluminum nitrate nonahydrate	= 3671 mg/kg (Rat)		
White mineral oil	> 5000 mg/kg (Rat)	-	-

Chronic Toxicity

Chronic Toxicity Repeated contact may cause allergic reactions in very susceptible persons.

Carcinogenicity Occupational health effects due to inhalation of mineral dusts incorporating crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc) graphite or coal unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Aluminum nitrate nonahydrate				X
White mineral oil	A2			
Paraffin oils	A2	Group 3 Group 1		X
Calcined kaolin clay		Group 2B		X
Isopropyl alcohol		Group 3		X

IARC: (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Sensitization May cause sensitization of susceptible persons.

Target Organ Effects Eyes. Respiratory system. Skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Solvent naphtha (petroleum), medium aliphatic	EC50 96 h: = 450 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 800 mg/L static (Pimephales promelas)		EC50 48 h: > 100 mg/L (Daphnia magna)
Paraffinic, naphthenic solvent		LC50: 45 mg/L Pimephales promelas 96 h flow-through LC50: 2.2 mg/L Lepomis macrochirus 96 h static LC50: 2.4 mg/L Oncorhynchus mykiss 96 h static		LC50 96 h: = 4720 mg/L (Daphnia magna)
Glycerol	-	LC50: 51-57 ml/L Oncorhynchus mykiss 96 h static	-	EC50 24 h: > 500 mg/L (Daphnia magna)
White mineral oil		LC50 96 h: > 10000 mg/L (Lepomis macrochirus)		
Isopropyl alcohol	EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
Chemical Name		Log Pow		
Glycerol		-1.76		
White mineral oil		6.006		
Isopropyl alcohol		0.05		

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to state and Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste pursuant to Federal regulations, and the applicable state requirements for the specific area of disposal. Consult the appropriate state, regional, or local regulations for additional requirements

Contaminated Packaging

Dispose of in accordance with local regulations.

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Calcined kaolin clay	Toxic soluble Toxic
Isopropyl alcohol	Toxic Ignitable

14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated.
<u>TDG</u>	Not regulated.
<u>MEX</u>	Not regulated.
<u>ICAO</u> Special Provisions	Not regulated. None.
<u>IATA</u> Special Provisions	Not regulated. None.
<u>IMDG/IMO</u> Special Provisions	Not regulated. None.
<u>RID</u> Special Provisions	Not regulated. None.
<u>ADR</u> Special Provisions	Not regulated. None.
<u>ADN</u>	Not regulated.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Aluminum oxide	1344-28-1	7	1.0
Aluminum nitrate nonahydrate	7784-27-2	1.75	1.0
Calcined kaolin clay	66402-68-4	<1	1.0
Isopropyl alcohol	67-63-0	0.5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

Calcined kaolin clay		X		
----------------------	--	---	--	--

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Solvent naphtha (petroleum), medium aliphatic	X				
Aluminum oxide	X	X	X		X
Glycerol	X	X	X	-	X
Aluminum nitrate nonahydrate			X		
Calcined kaolin clay			X		X
Paraffin oils	X	X	X		X
White mineral oil	X	X	X		X
Isopropyl alcohol	X	X	X		X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Aluminum oxide		Mexico: TWA= 10 mg/m ³
Glycerol		Mexico: TWA 10 mg/m ³
Aluminum nitrate nonahydrate		Mexico: TWA 2 mg/m ³
Calcined kaolin clay		Mexico: TWA 5 mg/m ³ Mexico: TWA 0.2 mg/m ³ Mexico: STEL 10 mg/m ³
Paraffin oils		Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³
White mineral oil		Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³
Isopropyl alcohol		Mexico: TWA 400 ppm Mexico: TWA 980 mg/m ³ Mexico: STEL 500 ppm Mexico: STEL 1225 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials



Component	NPRI
-----------	------

Isopropyl alcohol 67-63-0 (0.1-1)	X
--	---

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 21-Sep-2012
Revision Date 26-Dec-2012
Revision Note Product Code change, Name change.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet