

Issuing Date 22-Oct-2009

Revision Date 24-May-2015

Revision Number 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Mothers PowerPlastic 4Lights

Other means of identification

Product Code(s) 08808, 38808

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Car care

Uses advised against No information available

Supplier's details

Supplier Address
MOTHERS POLISHES WAXES CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827

Emergency telephone number

Emergency Telephone Number Chemtrec Phone: 1-800-424-9300 (within the U.S.) or +1 703-527-3887 (outside the U.S.)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Skin Sensitization	Category 1
--------------------	------------

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word	Warning
Hazard Statements	
• May cause an allergic skin reaction	



Appearance White **Physical State** Liquid. **Odor** Perfume

Precautionary Statements

Prevention

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective gloves.

General Advice

- Specific treatment (see supplemental instructions on the administration of antidotes on this label)

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.

Storage

- None

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Prolonged or repeated contact may dry skin and cause irritation
 Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Deodorized kerosene	8008-20-6	10-25	*
Calcined kaolin clay	66402-68-4	10-25	*
Isopropyl alcohol	67-63-0	< 10	*
Siloxanes and Silicones, dimethyl, [[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxy]-terminated	71750-80-6	1-5	*
Mineral Spirits	8052-41-3	< 10	*
D-Limonene	5989-27-5	< 10	*

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

4. FIRST AID MEASURES

Description of necessary first-aid measures

- General Advice** May produce an allergic reaction. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
- Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin Contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician.
Protection of First-aiders	Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects May cause allergic skin reaction.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Dry powder. Dry chemical.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

May cause sensitization by skin contact. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Soak up with inert absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

Incompatible Products Acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Deodorized kerosene 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S*	-	TWA: 100 mg/m ³
Calcined kaolin clay 66402-68-4	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr TWA: 0.2 mg/m ³ Mn	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
Mineral Spirits 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³ (vacated)	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³

Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.
Skin and Body Protection Wear protective gloves/clothing.
Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	Liquid.	Appearance	White.
Odor	Perfume.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	9.0	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	93.3 °C	None known
Flash Point	> 105 °C / > 221.3 °F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	1.008	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	600-900 cps	None known
Flammable Properties	Not flammable	
Explosive Properties	No data available	
Oxidizing Properties	No data available	
<u>Other information</u>		
VOC Content (%)	No data available	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Do not freeze. Heat, flames and sparks.

Incompatible materials

Acids. Strong oxidizing agents.

Hazardous decomposition products

Carbon oxides. None under normal use. Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Avoid breathing vapors or mists. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	May cause sensitization of susceptible persons. Repeated exposure may cause skin dryness or cracking.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Deodorized kerosene	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Isopropyl alcohol	= 4396 mg/kg (Rat)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Mineral Spirits	-	-	-
D-Limonene	5000 mg/kg (Rat)	>5000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Allergic skin reactions or irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization	May cause sensitization of susceptible persons.
Mutagenic Effects	No information available.
Carcinogenicity	Occupational health effects due to inhalation of mineral dusts incorporating crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc) graphite or coal unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Deodorized kerosene	A3	Group 3		
Calcined kaolin clay				X
Isopropyl alcohol		Group 3		
D-Limonene		Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity	This product does not contain any known or suspected reproductive hazards.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	Repeated exposure may cause skin dryness or cracking. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.
Target Organ Effects	Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Gastrointestinal tract (GI).
Aspiration Hazard	No information available.

Numerical measures of toxicity - Product*The following values are calculated based on chapter 3.1 of the GHS document:*

LD50 Oral	77256 mg/kg; Acute toxicity estimate
LD50 Dermal	224950 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropyl alcohol 67-63-0	EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
D-Limonene 5989-27-5		LC50 96 h: 0.619 - 0.796 mg/L flow-through (Pimephales promelas) LC50 96 h: = 35 mg/L (Oncorhynchus mykiss)		

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Isopropyl alcohol	0.05

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of in accordance with local regulations.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Calcined kaolin clay	Toxic soluble Toxic
Isopropyl alcohol	Toxic Ignitable
D-Limonene	Toxic

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Not determined

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Calcined kaolin clay	66402-68-4	10-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Calcined kaolin clay		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Methyl alcohol	67-56-1	Developmental
Diethanolamine	111-42-2	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Deodorized kerosene	X	X	X		X
Calcined kaolin clay			X		X
Isopropyl alcohol	X	X	X		X
Mineral Spirits	X	X	X		X
D-Limonene	X			X	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazard 2	Flammability 1	Physical Hazard 0	

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	22-Oct-2009
Revision Date	24-May-2015
Revision Note	Update to Format.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet