

Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 23-5568-3
 Version Number:
 7.00

 Issue Date:
 08/29/18
 Supercedes Date:
 01/07/15

SECTION 1: Identification

1.1. Product identifier

3MTM Quick Wax, 39034, 39034S

Product Identification Numbers

ID Number UPC ID Number UPC

LB-K100-0377-9 60-4550-3270-0

60-4550-3379-9 60-4550-6623-7 00051131390348

60-4550-6642-7 00051131390348

7000042719, 7010364390

1.2. Recommended use and restrictions on use

Recommended use

Automotive, ENHANCE APPEARANCE OF AUTOMOTIVE SURFACE

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Page 1 of 9

Symbols

Not applicable.

Pictograms

Not applicable.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 100 Trade Secret *
Carnauba Wax	8015-86-9	0.1 - 1 Trade Secret *
Isopropyl Alcohol	67-63-0	0.1 - 1 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

No need for first aid is anticipated.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

TOT THE COMPONENT.				
Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human
				carcin
Isopropyl Alcohol	67-63-0	OSHA	TWA:980 mg/m3(400 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure

esse general anation ventuation and of focal exhaust ventuation to control and of focal exhaust exhaust ventuation to control and of focal exhaust ventuat

Page 3 of

Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Tan/Brown Color slight solvent odor

Odor threshold No Data Available

pH 8.5 - 9.2 Melting point Not Applicable Boiling Point 212 °F

Flash Point > 212 °F [Test Method: Closed Cup]

Evaporation rate

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

Vapor Density

No Data Available
Density

0.985 - 1.0 g/ml

Specific Gravity 0.985 - 1.0 [Ref Std:WATER=1]

Solubility in Water Complete

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity1 - 20 centipoise

Hazardous Air Pollutants 0.17 % weight [Test Method: Calculated]

Molecular weight No Data Available

Volatile Organic Compounds12 g/l [*Test Method*:calculated SCAQMD rule 443.1] **Volatile Organic Compounds**1.2 % weight [*Test Method*:calculated per CARB title 2]

Percent volatile 99 % weight

VOC Less H2O & Exempt Solvents 379 g/l [Test Method:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

Page 4 of

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Page 5 of 9

08/29/18

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation- Vapor (4	Rat	LC50 72.6 mg/l
	hours)		
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal	No significant irritation
Carnauba Wax	Professio nal	No significant irritation
	judgeme nt	

Serious Eve Damage/Irritation

Name	Species	Value
Isopropyl Alcohol	Rabbit	Severe irritant
Carnauba Wax	Professio nal judgeme nt	No significant irritation

Skin Sensitization

Name	Species	Value
Isopropyl Alcohol	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

U	er in Cen Wutagementy		
N	ame	Route	Value
Is	sopropyl Alcohol	In Vitro	Not mutagenic
Is	sopropyl Alcohol	In vivo	Not mutagenic

Carcinogenicity

euremogemeny			
Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesi s
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

pecine target organ toxicity - single exposure							
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration	
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available		
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available		
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours	
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse	

Specific Target Organ Toxicity - repeated exposure

speeme ranger organi		, <u> </u>	T			
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Page 7 of

3MTM Quick Wax, 39034, 39034S

08/29/18

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical	Hazards

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	C.A.S. No.	Listing
Arsenic	None	Carcinogen
Cadmium	None	Male reproductive toxin
Cadmium	None	Carcinogen
Cadmium	None	Developmental Toxin
Cobalt	None	Carcinogen
Lead	None	Female reproductive toxin
Lead	None	Male reproductive toxin
Lead	None	Carcinogen
Lead	None	Developmental Toxin
Mercury	None	Developmental Toxin
Nickel	None	Carcinogen
Ethylene Glycol	107-21-1	Developmental Toxin

15.3. Chemical Inventories

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

Page 8 of 9

3MTM Quick Wax, 39034, 39034S

08/29/18

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 23-5568-3
 Version Number:
 7.00

 Issue Date:
 08/29/18
 Supercedes Date:
 01/07/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 9 of 9