



# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 1/25/2019 Revision date: 1/25/2022 Supersedes: 1/11/2019 Version: 1.3

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : HEET® Gas Line Antifreeze Line  
Synonym : 584402  
Part numbers : 28201; 28203; 28205; 28213; 28219

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Gold Eagle Co  
4400 S Kildare Ave  
Chicago, IL, 60632-4372  
T 773-376-4400  
<https://www.goldeagle.com/>

#### 1.4. Emergency telephone number

Emergency number : INFOTrac: 1-800-535-5053

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

|   |      |                                   |
|---|------|-----------------------------------|
| Flammable liquids Category 2                                | H225 | Highly flammable liquid and vapor |
| Acute toxicity (oral) Category 4                            | H302 | Harmful if swallowed              |
| Acute toxicity (inhalation:dust,mist) Category 2            | H330 | Fatal if inhaled                  |
| Specific target organ toxicity (single exposure) Category 1 | H370 | Causes damage to organs           |

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor  
H302 - Harmful if swallowed  
H330 - Fatal if inhaled  
H370 - Causes damage to organs

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P284 - [In case of inadequate ventilation] wear respiratory protection.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P307+P311 - If exposed: Call a poison center/doctor.  
P310 - Immediately call a poison center or doctor.  
P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P330 - Rinse mouth.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name     | Product identifier | %     | GHS US classification   |
|----------|--------------------|-------|---|
| Methanol | CAS-No.: 67-56-1   | ≤ 100 | Flam. Liq. 2, H225<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 3 (Inhalation), H331<br>STOT SE 1, H370 |

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.  
Call a doctor.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

No additional information available

# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| HEET® Gas Line Antifreeze Line             |  |
|--|--|
| No additional information available        |  |
| Methanol (67-56-1)                         |  |
| USA - ACGIH - Occupational Exposure Limits |  |
| Local name                                 | Methanol   |
| ACGIH OEL TWA [ppm]                        | 200 ppm  |
| ACGIH OEL STEL [ppm]                       | 250 ppm  |
| Remark (ACGIH)                             | TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI |
| Regulatory reference                       | ACGIH 2019   |
| USA - OSHA - Occupational Exposure Limits  |  |
| Local name                                 | Methyl alcohol   |
| OSHA PEL (TWA) [1]                         | 260 mg/m³  |
| OSHA PEL (TWA) [2]                         | 200 ppm  |
| Regulatory reference (US-OSHA)             | OSHA Annotated Table Z-1   |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

|                                   |
|-----------------------------------|
| <b>Hand protection:</b>           |
| Protective gloves                 |
| <b>Eye protection:</b>            |
| Safety glasses                    |
| <b>Skin and body protection:</b>  |
| Wear suitable protective clothing |
| <b>Respiratory protection:</b>    |
| Wear respiratory protection.      |

Personal protective equipment symbol(s):



# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |  |
|---|--|
| Physical state                                  | : Liquid   |
| Color   | : Mixture contains one or more component(s) which have the following colour(s):<br>Colourless Colourless to light yellow   |
| Odor  | : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.<br>Mixture contains one or more component(s) which have the following odour:<br>Petroleum-like odour Sweet odour Aromatic odour Characteristic odour Mild odour Pleasant odour Alcohol odour Commercial/unpurified substance: irritating/pungent odour |
| Odor threshold                                  | : No data available  |
| pH  | : No data available  |
| Melting point                                   | : Not applicable   |
| Freezing point                                  | : No data available  |
| Boiling point                                   | : 147 °F   |
| Flash point                                     | : 56 °F  |
| Relative evaporation rate (butyl acetate=1)     | : No data available  |
| Flammability (solid, gas)                       | : Not applicable.  |
| Vapor pressure                                  | : 96   |
| Relative vapor density at 20 °C                 | : No data available  |
| Relative density                                | : 0.791  |
| Solubility                                      | : Water: 100   |
| Partition coefficient n-octanol/water (Log Pow) | : No data available  |
| Auto-ignition temperature                       | : No data available  |
| Decomposition temperature                       | : No data available  |
| Viscosity, kinematic                            | : 3 – 5 (40 °C)  |
| Viscosity, dynamic                              | : No data available  |
| Explosion limits                                | : Lower explosion limit: 2<br>Upper explosion limit: 12.7  |
| Explosive properties                            | : No data available  |
| Oxidizing properties                            | : No data available  |

#### 9.2. Other information

VOC content : 100

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Highly flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Fatal if inhaled.

#### HEET® Gas Line Antifreeze Line

|                     |                        |
|---------------------|------------------------|
| ATE US (oral)       | 1187 mg/kg body weight |
| ATE US (dust, mist) | 0.5 mg/l/4h            |

#### Methanol (67-56-1)

|                       |   |
|-----------------------|---|
| LD50 oral rat         | 1187 – 2769 mg/kg body weight (BASF test, Rat, Male/female, Weight of evidence, Aqueous solution, Oral, 7 day(s)) |
| LD50 dermal rabbit    | 17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)   |
| LC50 Inhalation - Rat | 128.2 mg/l air (BASF test, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours))                       |

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Causes damage to organs.

#### Methanol (67-56-1)

|                      |                          |
|----------------------|--------------------------|
| STOT-single exposure | Causes damage to organs. |
|----------------------|--------------------------|

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified  
Viscosity, kinematic : 3 – 5 (40 °C)

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

#### Methanol (67-56-1)

|                      |  |
|----------------------|--|
| LC50 - Fish [1]      | 15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)                                 |
| EC50 - Crustacea [1] | 18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 algae          | 22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)               |

# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.2. Persistence and degradability

#### Methanol (67-56-1)

|                                 |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.6 – 1.12 g O <sub>2</sub> /g substance                           |
| Chemical oxygen demand (COD)    | 1.42 g O <sub>2</sub> /g substance                                 |
| ThOD                            | 1.5 g O <sub>2</sub> /g substance                                  |

### 12.3. Bioaccumulative potential

#### Methanol (67-56-1)

|   |   |
|---|---|
| BCF - Fish [1]                                  | 1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | -0.77 (Experimental value)  |
| Partition coefficient n-octanol/water (Log Kow) | -0.77   |
| Bioaccumulative potential                       | Low potential for bioaccumulation (BCF < 500).                                  |

### 12.4. Mobility in soil

#### Methanol (67-56-1)

|  |  |
|--|--|
| Surface tension  | 0.023 N/m (20 °C)                                    |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.088 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil   | Highly mobile in soil.                               |

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

DOT NA No : Not applicable  
UN-No. (TDG) : Not applicable  
UN-No. (IMDG) : 1230  
UN-No. (IATA) : 1230

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Consumer commodity  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : METHANOL  
Proper Shipping Name (IATA) : Methanol

# HEET® Gas Line Antifreeze Line


## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : LTD QTY  
Hazard labels (DOT) : LTD QTY



#### TDG

Transport hazard class(es) (TDG) : Not applicable

#### IMDG

Transport hazard class(es) (IMDG) : 3 (6.1)  
Hazard labels (IMDG) : 3, 6.1



#### IATA

Transport hazard class(es) (IATA) : 3 (6.1)  
Hazard labels (IATA) : 3, 6.1



### 14.4. Packing group

Packing group (DOT) : II  
Packing group (TDG) : Not applicable  
Packing group (IMDG) : II  
Packing group (IATA) : II

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

**DOT**  
DOT Special Provisions (49 CFR 172.102) : 222 - Shipments offered for transportation by aircraft may not be reclassified as ORM-D.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 156;306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 156;306  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 30 kg gross  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 11 - Keep away from heat and open flame



# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### TDG

No data available

### IMDG

|                                    |  |
|------------------------------------|--|
| Special provision (IMDG)           | : 279  |
| Limited quantities (IMDG)          | : 1 L  |
| Excepted quantities (IMDG)         | : E2   |
| Packing instructions (IMDG)        | : P001   |
| IBC packing instructions (IMDG)    | : IBC02  |
| Tank instructions (IMDG)           | : T7   |
| Tank special provisions (IMDG)     | : TP2  |
| EmS-No. (Fire)                     | : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  |
| EmS-No. (Spillage)                 | : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  |
| Stowage category (IMDG)            | : B  |
| Flash point (IMDG)                 | : 12°C c.c.  |
| Properties and observations (IMDG) | : Colourless, volatile liquid. Flashpoint: 12°C c.c. Explosive limits: 6% to 36.5% Miscible with water. Toxic if swallowed; may cause blindness. Avoid skin contact. |

### IATA

|  |               |
|--|---------------|
| Transport regulations (IATA)                 | : Not subject |
| PCA Excepted quantities (IATA)               | : E1          |
| PCA Limited quantities (IATA)                | : Y341        |
| PCA limited quantity max net quantity (IATA) | : 1L          |
| PCA packing instructions (IATA)              | : 352         |
| PCA max net quantity (IATA)                  | : 1L          |
| CAO packing instructions (IATA)              | : 364         |
| CAO max net quantity (IATA)                  | : 60L         |
| Special provision (IATA)                     | : A113        |
| ERG code (IATA)                              | : 3L          |

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

| Name     | CAS-No. | Listing | Commercial status | Flags |
|----------|---------|---------|-------------------|-------|
| Methanol | 67-56-1 | Present | Active            |       |

#### Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313  
Listed on EPA Hazardous Air Pollutant (HAPS)

|           |         |
|-----------|---------|
| CERCLA RQ | 5000 lb |
|-----------|---------|

### 15.2. International regulations

#### CANADA

#### Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

# HEET® Gas Line Antifreeze Line

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### EU-Regulations

No additional information available

### National regulations

No additional information available

### 15.3. US State regulations

| Methanol (67-56-1)                                    |   |   |   |                                  |   |
|---|---|---|---|----------------------------------|---|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL)             |
| No  | Yes   | No  | No  |                                  | 47000 µg/day (inhalation); 23,000 µg/day (oral) |

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/25/2022

| Full text of H-phrases |                                   |
|------------------------|-----------------------------------|
| H225                   | Highly flammable liquid and vapor |
| H302                   | Harmful if swallowed              |
| H330                   | Fatal if inhaled                  |
| H331                   | Toxic if inhaled                  |
| H370                   | Causes damage to organs           |

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.