



SAFETY DATA SHEET

1. Identification

Product identifier Gunk Engine Brite Engine Cleaner - Foamy

Other means of identification

SDS number FEB1CA
Part No. FEB1CA
Tariff code 3402.20.5100

Recommended use Engine Cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blaster LLC
Address 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA
Telephone T(216)901-5800
Website F (216)901-5801
E-mail www.blastercorp.com
Emergency phone number Chemtrec (800) 424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1
Carcinogenicity Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Pressurized container: May burst if heated. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) GHS Level 3 Non-flammable aerosol (version 7 - July 2017)

Supplemental information NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	70 - < 80
Isobutyl Heptyl Ketone		123-18-2	5 - < 10
Petroleum Gases, Liquefied, Sweetened		68476-86-8	5 - < 10
C9-C15 Heavy Aromatic Hydrocarbons		64742-95-6	1 - < 3
Poly(oxyethylene) Sorbitol Hexaoleate		57171-56-9	1 - < 3
Trimethylbenzene		25551-13-7	1 - < 3
Tripropylene Glycol Monomethyl Ether		25498-49-1	1 - < 3
1,2,3-Trimethylbenzene		526-73-8	< 1
1,2,4-Trimethylbenzene		95-63-6	< 1
1,3,5-Trimethylbenzene		108-67-8	< 1
Alcohols, C12-14, Secondary, Ethoxylated		84133-50-6	< 1
Xanthan Gum		11138-66-2	< 1
Oleic Acid		112-80-1	< 0.3
2,6,8-trimethyl-4-nonanol		123-17-1	< 0.2
Cumene		98-82-8	< 0.2
Tetrasodium Ethylenediaminetetraacetate		64-02-8	< 0.2
Triethanolamine		102-71-6	< 0.2
Diethanolamine		111-42-2	< 0.1
Glyoxal		107-22-2	< 0.1
Sodium Chloride		7647-14-5	< 0.1
Toluene		108-88-3	< 0.1
Xylene		1330-20-7	< 0.1
Other components below reportable levels			< 0.2

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Containers should be cooled with water to prevent vapor pressure build up.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol. Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
C9-C15 Heavy Aromatic Hydrocarbons (CAS 64742-95-6)	PEL	400 mg/m3 100 ppm
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,3-Trimethylbenzene (CAS 526-73-8)	TWA	25 ppm	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
1,3,5-Trimethylbenzene (CAS 108-67-8)	TWA	25 ppm	
Cumene (CAS 98-82-8)	TWA	50 ppm	
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
Glyoxal (CAS 107-22-2)	TWA	0.1 mg/m3	Inhalable fraction and vapor.
Toluene (CAS 108-88-3)	TWA	20 ppm	
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3	
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,3-Trimethylbenzene (CAS 526-73-8)	TWA	125 mg/m3
		25 ppm
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
		25 ppm
1,3,5-Trimethylbenzene (CAS 108-67-8)	TWA	125 mg/m3
		25 ppm
C9-C15 Heavy Aromatic Hydrocarbons (CAS 64742-95-6)	TWA	400 mg/m3
		100 ppm
Cumene (CAS 98-82-8)	TWA	245 mg/m3
		50 ppm
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3
		3 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm
Trimethylbenzene (CAS 25551-13-7)	TWA	125 mg/m3
		25 ppm
Xylene (CAS 1330-20-7)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
		100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Glyoxal (CAS 107-22-2)	TWA	0.1 mg/m3	Inhalable fraction and vapor.
		0.042 ppm	Inhalable fraction and vapor.

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
Diethanolamine (CAS 111-42-2)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2)	Can be absorbed through the skin.
-------------------------------	-----------------------------------

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece. Applicable for industrial settings only.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Applicable for industrial settings only.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Applicable for industrial settings only.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Applicable for industrial settings only.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Aerosol.
Physical state	Liquid.
Form	Aerosol.
Color	milky white
Odor	Aromatic.
Odor threshold	Not available.
pH	8.5 - 9.5
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	157.0 °F (69.4 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	64 - 74 hPa psig
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Aerosol foam	
Flame duration	< 1 seconds
Flame height	< 4 cm
Density	8.17 lbs/gal
Explosive properties	Not explosive.
Flammability (flash back)	No
Flammability class	Combustible IIIA estimated
Heat of combustion	7.42 kJ/g estimated
Heat of combustion (NFPA 30B)	7.42 kJ/g estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.975 - 0.995
VOC	9.2 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
1,2,3-Trimethylbenzene (CAS 526-73-8)		
Acute		
Oral		
LD50	Rat	8970 mg/kg
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Oral		
LD50	Rat	6 g/kg
1,3,5-Trimethylbenzene (CAS 108-67-8)		
Acute		
Oral		
LD50	Rat	8970 mg/kg 3280 mg/kg
C9-C15 Heavy Aromatic Hydrocarbons (CAS 64742-95-6)		
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 4.96 mg/l, 4 Hours
Oral		
LD50	Rat	14060 mg/kg 4820 mg/kg
Cumene (CAS 98-82-8)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Mouse	10 mg/l, 7 Hours
Oral		
LD50	Rat	2260 mg/kg

Components	Species	Test Results
Diethanolamine (CAS 111-42-2)		
<u>Acute</u>		
Oral		
LD50	Rat	710 mg/kg
Glyoxal (CAS 107-22-2)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 800 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 1.3 mg/l, 4 Hours 2.47 mg/l, 4 Hours
Oral		
LD50	Rat	762 mg/kg
Oleic Acid (CAS 112-80-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 3000 mg/kg
Oral		
LD50	Rat	74 g/kg
Sodium Chloride (CAS 7647-14-5)		
<u>Acute</u>		
Oral		
LD50	Rat	3000 mg/kg
Tetrasodium Ethylenediaminetetraacetate (CAS 64-02-8)		
<u>Acute</u>		
Oral		
LD50	Rat	> 2000 mg/kg
Toluene (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	12.5 - 28.8 mg/l, 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Triethanolamine (CAS 102-71-6)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	6400 mg/kg
Trimethylbenzene (CAS 25551-13-7)		
<u>Acute</u>		
Oral		
LD50	Rat	8970 mg/kg
Tripropylene Glycol Monomethyl Ether (CAS 25498-49-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	15440 mg/kg, 24 Hours

Components	Species	Test Results
Oral LD50	Rat	3400 mg/kg
Xylene (CAS 1330-20-7)		
Acute Dermal LD50	Rabbit	12130 mg/kg, 24 Hours
Inhalation LC50	Rat	6350 mg/l, 4 Hours
Oral LD50	Rat	3523 - 8600 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
ACGIH sensitization		
GLYOXAL, INHALABLE FRACTION AND VAPOR (CAS 107-22-2)		Dermal sensitization
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	May cause cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	
Diethanolamine (CAS 111-42-2)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Triethanolamine (CAS 102-71-6)	3 Not classifiable as to carcinogenicity to humans.	
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours
1,3,5-Trimethylbenzene (CAS 108-67-8)		
Aquatic		
Fish	LC50	Goldfish (Carassius auratus) 9.89 - 15.05 mg/l, 96 hours

Components	Species		Test Results
C9-C15 Heavy Aromatic Hydrocarbons (CAS 64742-95-6)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
Cumene (CAS 98-82-8)			
Aquatic			
Crustacea	EC50	Brine shrimp (Artemia sp.)	3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.7 mg/l, 96 hours
Diethanolamine (CAS 111-42-2)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	61.8 - 86.04 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours
Glyoxal (CAS 107-22-2)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	215 mg/l, 96 hours
Oleic Acid (CAS 112-80-1)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	205 mg/l, 96 hours
Sodium Chloride (CAS 7647-14-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	340.7 - 469.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	6020 - 7070 mg/l, 96 hours
Tetrasodium Ethylenediaminetetraacetate (CAS 64-02-8)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Triethanolamine (CAS 102-71-6)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	10610 - 13010 mg/l, 96 hours
Xanthan Gum (CAS 11138-66-2)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	320 - 560 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Cumene	3.66
Diethanolamine	-1.43
Toluene	2.73
Triethanolamine	-1

Partition coefficient n-octanol / water (log Kow)

Xylene

3.12 - 3.2

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations**Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information**DOT****UN number**

UN1950

UN proper shipping name

Aerosol, non-flammable, MARINE POLLUTANT, Limited Quantity

Transport hazard class(es)**Class**

2.2

Subsidiary risk

-

Packing group

Not available.

Environmental hazards**Marine pollutant**

Yes

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

IATA**UN number**

UN1950

UN proper shipping name

Aerosol, non-flammable, Limited Quantity

Transport hazard class(es)**Class**

2.2

Subsidiary risk

-

Packing group

Not available.

Environmental hazards

No.

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

IMDG**UN number**

UN1950

UN proper shipping name

Aerosols, MARINE POLLUTANT (1,2,3-trimethylbenzene), Limited Quantity

Transport hazard class(es)**Class**

2.2

Subsidiary risk

-

Packing group

Not available.

Environmental hazards**Marine pollutant**

Yes

EmS

F-D, S-U

Special precautions for user


Read safety instructions, SDS and emergency procedures before handling.

1,2,3-trimethylbenzene


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

DOT; IMDG



IATA



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8)	Listed.
Diethanolamine (CAS 111-42-2)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No (Exempt)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Cumene (CAS 98-82-8)

Diethanolamine (CAS 111-42-2)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including diethanolamine, which are known to the State of California to cause cancer, and toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8) Listed: April 6, 2010

Diethanolamine (CAS 111-42-2) Listed: June 22, 2012

California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,3-Trimethylbenzene (CAS 526-73-8)
1,2,4-Trimethylbenzene (CAS 95-63-6)
1,3,5-Trimethylbenzene (CAS 108-67-8)
C9-C15 Heavy Aromatic Hydrocarbons (CAS 64742-95-6)
Cumene (CAS 98-82-8)
Diethanolamine (CAS 111-42-2)
Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)
Toluene (CAS 108-88-3)
Trimethylbenzene (CAS 25551-13-7)
Xylene (CAS 1330-20-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 09-19-2018

Material name: Gunk Engine Brite Engine Cleaner - Foamy

FEB1CA Version #: 03 Revision date: 02-24-2023 Issue date: 09-19-2018

SDS US

13 / 14

Revision date 02-24-2023
Version # 03
HMIS® ratings Health: 2*
Flammability: 0
Physical hazard: 0
NFPA ratings Health: 2
Flammability: 0
Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.