

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 03/28/2014 Revision date: 07/11/18 Version: 1.0

1.1. Product identifier

Product name : FVP LOW VOC 45 NON-CHLORINATED BRAKE CLEANER

Product code : FVPNCBCVOC45-55GAL

1.2.

Use of the substance/mixture : Brake Cleaner.

1.3.

Details of the supplier of the safety data sheet

Factory Motor Parts 1380 Corporate Center Curve, Suite 200 Eagan, MN 55121 1-866-387-3343

1.4. Emergency telephone number

Emergency number 24 hr Infotrac 1-800-535-5053

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 2
Skin irritation 2
Eye irritation 2A
Reproductive toxicity 2 (developmental)
Specific target organ toxicity - Single exposure 3
Specific target organ toxicity - Repeated exposure 2
Aspiration hazard 1

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)

GHS02

: Danger



GHS07



GHS08

Signal word (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)

- : Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated. May be fatal if swallowed and enters airways.
- : Keep away from heat/sparks/open flames/hot surfaces.— No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool. Dispose of contents and container in accordance with all

22



55 GALLON local, regional, national and international regulations.

Safety Data Sheet

No additional information available ording to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Unknown acute toxicity (GHS-US)

17 % of the mixture consists of ingredient(s) of unknown acute toxicity.

03/28/2014 EN (English) Page 1





3.1.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Acetone	(CAS No) 67-64-1	40 - 70	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Heptane, branched, cyclic and linear	(CAS No) 426260-76-6	15 - 40	Flam. Liq. 2 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
n-Heptane	(CAS No) 142-82-5	10 - 30	Flam. Liq. 2 Skin Irrit. 2 STOT SE 3
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	7 - 13	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Toluene	(CAS No) 108-88-3	0.5 - 1.5	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1
The exact percentage (concentration) of composition	on has been withheld as a trade secret in accorda	nce with paragraph (i) of	§1910.1200.

4.1. Description of first aid measures

First-aid measures after ingestion

Symptoms/injuries after skin contact

Symptoms/injuries after eye contact

Symptoms/injuries after ingestion

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to

neasures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.

: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2.

Symptoms/injuries after inhalation : May cause drowsiness, dizziness and central nervous system depression. May cause respiratory irritation.

: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3.

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

5.1. Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2.

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA). Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.



General measures

FVP LOW VOC 45 NON-CHLORINATED BRAKE CLEANER

55 GALLON

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to Safety Data Sheetunnecessary and unprotected personnel. Eliminate sources of ignition. according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.



55 GALLON

6.2. Safety Data Sheet

For containment according to the Hazard Com Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable

container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal

Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3.

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not

breathe gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-

ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2.

Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place.

Store locked up. Keep cool. Keep away from heat, sparks, and flame.

7.3.

Not available.

8.1. Control parameters

Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

n-Heptane (142-82-5)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear chemically resistant protective gloves.

8.2.



55 GALLON: Safety glasses or goggles are recommended when using product.

Safety Data SheeWear suitable protective clothing.

according to the Hazard Com. A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Eye protection Skin and body protection Respiratory protection



55 GALLON

Environmental exposure controls

Safety Data Sheet
Other information

Maintain levels below Community environmental protection thresholds.

Other information

Maintain levels below Community environmental protection thresholds.

Safety Data Sheet
On on teat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and

safety practices.

: No data available.

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance · Clear Colour : Colourless.

Solvent Odour

: No data available. Odour threshold рН : No data available. Relative evaporation rate (butylacetate=1) : No data available. Melting point : No data available. Freezing point : No data available.

Boiling point : ~ 56 °C (~ 133 °F) (Acetone) Flash point : ~ -20 °C (~ -4 °F) (Acetone)

Self ignition temperature : No data available. Decomposition temperature : No data available. Flammability (solid, gas) : Flammable Vapour pressure : No data available. Relative vapour density at 20 °C · No data available Relative density : 0.730 - 0.745 Solubility : No data available. Log Pow : No data available. Log Kow : No data available. Viscosity, kinematic : No data available. Viscosity, dynamic : No data available. Explosive properties : No data available. Oxidising properties : No data available.

No additional information available

10.1. Reactivity

Explosive limits

No dangerous reaction known under conditions of normal use.

10.2. **Chemical stability**

Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

10.5. Incompatible materials

Acids. Amines. Bases. Oxidizers.

10.6. **Hazardous decomposition products**

May include, and are not limited to: oxides of carbon.

11.1. Information on toxicological effects

Acute toxicity : Not classified



	JO OALLON	
4655	0-6-6-0-0-	-1
LD50 oral rat	Safety Data Sne	2000 mg/kg
LD50 dermal rabbit		> 2000 mg/kg
LC50 inhalation rat (mg/l)		> 20 mg/l/4h
Acetone (67-64-1)		
LD50 oral rat		5800 mg/kg
LC50 inhalation rat (mg/l)		50100 mg/m³/8h



55 GALLON

n-Heptane (142-82-5) LD50 dermal rabbit	Safety Data She	et 3000:mg/kgandard (CFR29 1910.1200) HazCom 2012.
LC50 inhalation rat (mg/l)		103 g/m³/4h

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	> 1700 mg/kg
LC50 inhalation rat (ppm)	5000 ppm/4h
LC50 inhalation rat (mg/l)	47635 mg/l/4h

Toluene (108-88-3)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	12124 mg/kg	
LD50 dermal rabbit	8390 mg/kg	
LC50 inhalation rat (mg/l)	28.1 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation. Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met. Germ cell mutagenicity : Based on available data, the classification criteria are not met. : Based on available data, the classification criteria are not met. Carcinogenicity

Xylenes (o-, m-, p- isomers) (1330-20-7)

3 IARC group

Toluene (108-88-3)

IARC group 3

Reproductive toxicity : Suspected of damaging the unborn child. Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause drowsiness, dizziness and central nervous system depression. May cause respiratory

irritation.

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of

the skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and Symptoms/injuries after ingestion

cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

12.1. **Toxicity**

: May cause long-term adverse effects in the aquatic environment. Ecology - general

Persistence and degradability 12.2.

4655	
Persistence and degradability	Not established.

12.3. **Bioaccumulative potential**

4655		
Bioaccui	mulative potential	Not established.
12.4. Mobility in soil		

No additional information available

12.5. Other adverse effects

No additional information available



55 GALLON 13.1. **Waste treatment methods**

Waste disposal recommendations to the Hazard Commendations. The generation of waste should be avoided or minimized wherever possible.

Additional information

: Handle empty containers with care because residual vapours are flammable.



Safety Data Sheet

In accordance with DOT

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

14.1. UN number

UN-No. : UN1993

14.2. UN proper shipping name

Proper Shipping Name : Flammable liquids, n.o.s. (Acetone, Heptane)

Department of Transportation Hazard Classes : 3

Hazard labels :

3

Packing group (DOT) : I

14.

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

15.1. US Federal regulations

Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

Heptane, branched, cyclic and linear (426260-76-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

n-Heptane (142-82-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

15.2. US State regulations

4655

State or local regulations

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

IARC International Agency for Research on Cancer.



The Confide	FVP LOW VOC 45 NON-CHLORINATED BRAKE CLEANER 55 GALLON 1 - Carcinogenic to humans; 25 Probably carcinogenic to humans; 28 Probably carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans.
NTP	National Toxicology Program.
	 1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration.



FVP LOW VOC 45 NON-CHLORINATED BRAKE CLEANER 55 GALLON

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.


Indication of changes : None.

Date of issue : 03/28/2014

Other information : None.

NFPA health hazard

NFPA fire hazard : 3
NFPA reactivity : 0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product