

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

### SECTION 1. IDENTIFICATION

Product name : MM TRANSEAL AUTO TRANS SEAL 12/12OZ  
Product code : M1512

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC  
Address : Dallas TX 75225  
Email Address : EHS@niteoproducts.com  
Telephone : 1-844-696-4836  
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : SEALER  
Restrictions on use : Use only outdoors or in a well-ventilated area.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitisation : Category 1  
Carcinogenicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :

Signal word : Danger

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

Hazard statements : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
IF ON SKIN: Wash with plenty of soap and water.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
If skin irritation or rash occurs: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.

**Storage:**  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.

**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

Distillates (petroleum)	64742-54-7	>= 70 - < 90
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 20 - < 30
tert-Butylbenzene	98-06-6	>= 10 - < 20
p-Diethylbenzene	105-05-5	>= 1 - < 5
1,2,3,5-tetramethylbenzene	527-53-7	>= 1 - < 5
1,2,3,4-tetramethylbenzene	488-23-3	>= 1 - < 5
Naphthalene	91-20-3	>= 1 - < 5
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5
1,2,3-Trimethylbenzene	526-73-8	>= 1 - < 5
Distillates (petroleum)	64742-55-8	>= 1 - < 5
Diethylbenzene	25340-17-4	>= 1 - < 5
Cumene	98-82-8	>= 1 - < 5
Benzene, 1,3-diethyl-	141-93-5	>= 1 - < 5
Substituted hydrocarbyl sulfide	Not Assigned	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

Suspected of causing cancer.  
Inhalation or ingestion of high levels of this material (or a component) may cause a hemolytic reaction. Complications of acute intravascular hemolysis include anemia, leukocytosis, fever, hemoglobinuria, jaundice, renal insufficiency, and sometimes disturbances in liver function.  
Fats, for example, baby oil on the skin or ingested oil, facilitate absorption of naphthalene.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Avoid breathing dust.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

**MOTOR MEDIC® TRANSEAL® AUTOMATIC  
TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Avoid contact with skin and eyes.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-54-7	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Solvent naphtha (petroleum), heavy arom.	64742-94-5	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
Naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m <sup>3</sup>	NIOSH REL
		ST	15 ppm 75 mg/m <sup>3</sup>	NIOSH REL
		TWA	10 ppm 50 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10 ppm 50 mg/m <sup>3</sup>	OSHA P0

**SAFETY DATA SHEET**



**MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
 Date of first issue: 05/27/2020

		STEL	15 ppm 75 mg/m3	OSHA P0
1,2,4-Trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
1,2,3-Trimethylbenzene	526-73-8	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
Distillates (petroleum)	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Diethylbenzene	25340-17-4	TWA	5 ppm	US WEEL
Cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

**Hazardous components without workplace control parameters**

Components	CAS-No.
tert-Butylbenzene	98-06-6
p-Diethylbenzene	105-05-5
1,2,3,5-tetramethylbenzene	527-53-7
1,2,3,4-tetramethylbenzene	488-23-3
Benzene, 1,3-diethyl-	141-93-5
Substituted hydrocarbyl sulfide	Not Assigned

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear as appropriate:  
Impervious clothing  
Safety shoes
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not smoke.  
When using do not eat or drink.
- 

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : not determined
- Odour : not determined
- Odour Threshold : not determined
- pH : not determined
- Melting point/freezing point : not determined
- Boiling point/boiling range : not determined
- Flash point : > 100 °C  
Value for Component
- Evaporation rate : not determined
- Flammability (solid, gas) : No data available
- Self-ignition : not determined
- Upper explosion limit / Upper flammability limit : not determined
- Lower explosion limit / Lower flammability limit : not determined
- Vapour pressure : not determined
- Relative vapour density : not determined
- Density : 0.8642 g/cm<sup>3</sup>
- Solubility(ies)  
Water solubility : not determined

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

Partition coefficient: n-octanol/water : not determined

Decomposition temperature : not determined

Viscosity  
  Viscosity, dynamic : not determined

  Viscosity, kinematic : not determined

Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon oxides

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Eye contact  
Skin contact  
Ingestion

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Components:

**Distillates (petroleum):**



**MOTOR MEDIC® TRANSEAL® AUTOMATIC  
TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**Solvent naphtha (petroleum), heavy arom.:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**tert-Butylbenzene:**

Acute oral toxicity : LD50 (Rat): 3,503 mg/kg

**1,2,3,5-tetramethylbenzene:**

Acute oral toxicity : LD50 (Rat): 5,157 mg/kg

**Naphthalene:**

Acute oral toxicity : LD50 (Mouse, male): 533 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,500 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**1,2,4-Trimethylbenzene:**

Acute oral toxicity : LD50 (Rat): 6 g/kg

Acute inhalation toxicity : LC50 (Rat): 10.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,440 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.  
Remarks: Information given is based on data obtained from similar substances.

**MOTOR MEDIC® TRANSEAL® AUTOMATIC  
TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

**1,2,3-Trimethylbenzene:**

- Acute oral toxicity : LD50 (Rat): 6 g/kg
- Acute inhalation toxicity : LC50 (Rat): > 10,200 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.  
Remarks: Information given is based on data obtained from similar substances.
- Acute dermal toxicity : LD50 (Rabbit): > 3,440 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Diethylbenzene:**

- Acute oral toxicity : LD50 (Rat, male and female): 2,050 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male): > 2100 ppm  
Exposure time: 7 h  
Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : LD50 (Rabbit, male and female): > 5,000 mg/kg

**Cumene:**

- Acute oral toxicity : LD50 (Rat): 2,910 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 8000 ppm  
Exposure time: 4 h  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:****Distillates (petroleum):**

Result: Possibly irritating to skin

**Solvent naphtha (petroleum), heavy arom.:**

Result: Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

**tert-Butylbenzene:**

Result: Irritating to skin.

**p-Diethylbenzene:**

Result: Possibly irritating to skin

**1,2,3,5-tetramethylbenzene:**

Result: Irritating to skin.

**1,2,3,4-tetramethylbenzene:**

Result: Irritating to skin.

**Naphthalene:**

Result: Possibly irritating to skin

**1,2,4-Trimethylbenzene:**

Result: Irritating to skin.

**1,2,3-Trimethylbenzene:**

Result: Irritating to skin.

**Distillates (petroleum):**

Result: Possibly irritating to skin

**Diethylbenzene:**

Species: Rabbit

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Irritating to skin.

GLP: yes

**Cumene:**

Result: No skin irritation

**Benzene, 1,3-diethyl-:**

Result: Irritating to skin.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

### **Components:**

#### **Distillates (petroleum):**

Result: No eye irritation  
Assessment: No eye irritation

#### **Solvent naphtha (petroleum), heavy arom.:**

Result: Possibly irritating to eyes

#### **tert-Butylbenzene:**

Result: Irritating to eyes.

#### **p-Diethylbenzene:**

Result: Irritating to eyes.

#### **1,2,3,5-tetramethylbenzene:**

Result: Irritating to eyes.

#### **1,2,3,4-tetramethylbenzene:**

Result: Irritating to eyes.

#### **Naphthalene:**

Result: Possibly irritating to eyes

#### **1,2,4-Trimethylbenzene:**

Result: Irritating to eyes.

#### **1,2,3-Trimethylbenzene:**

Result: Irritating to eyes.

#### **Distillates (petroleum):**

Result: Possibly irritating to eyes

#### **Diethylbenzene:**

Species: Rabbit  
Result: Possibly irritating to eyes  
GLP: yes

#### **Cumene:**

Result: No eye irritation

#### **Benzene, 1,3-diethyl-:**

Result: Irritating to eyes.

**MOTOR MEDIC® TRANSEAL® AUTOMATIC  
TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks: May cause allergic skin reaction.

**Components:****Solvent naphtha (petroleum), heavy arom.:**

Result: Not a skin sensitizer.

**1,2,4-Trimethylbenzene:**

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

**1,2,3-Trimethylbenzene:**

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

**Diethylbenzene:**

Test Type: Buehler Test

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

GLP: yes

**Cumene:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

**Substituted hydrocarbyl sulfide:**

Result: May cause sensitisation by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****1,2,4-Trimethylbenzene:**

Genotoxicity in vitro : Test Type: Ames test  
Result: negative

**MOTOR MEDIC® TRANSEAL® AUTOMATIC  
TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**1,2,3-Trimethylbenzene:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Method: OECD Test Guideline 474  
Result: negative

**Diethylbenzene:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse (male and female)  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

**Cumene:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Mouse  
Method: OECD Test Guideline 474  
Result: negative

**Carcinogenicity**

Suspected of causing cancer.

**Components:**
**Solvent naphtha (petroleum), heavy arom.:**

Carcinogenicity - Assessment : Suspected human carcinogens

**Naphthalene:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**Cumene:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies



**MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER**

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

---

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Components:**

**Distillates (petroleum):**

May be fatal if swallowed and enters airways.

**Solvent naphtha (petroleum), heavy arom.:**

May be fatal if swallowed and enters airways.

**1,2,4-Trimethylbenzene:**

May be fatal if swallowed and enters airways.

**1,2,3-Trimethylbenzene:**

May be fatal if swallowed and enters airways.

**Distillates (petroleum):**

May be fatal if swallowed and enters airways.

**Diethylbenzene:**

May be fatal if swallowed and enters airways.

**Cumene:**

May be fatal if swallowed and enters airways.

**Benzene, 1,3-diethyl-:**

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.



# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

Not regulated as a dangerous good

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Naphthalene	91-20-3	100	4283
Benzene	71-43-2	10	10 (D018)
Butanol normal	71-36-3	100	100 (F003)
Toluene	108-88-3	100	100 (F005)

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sulfur dioxide	7446-09-5	500	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version 1.1      Revision Date: 03/29/2023      SDS Number: 600000001820      Date of last issue: 05/27/2020  
Date of first issue: 05/27/2020

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitisation  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Naphthalene	91-20-3	>= 1 - < 5 %
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5 %
Cumene	98-82-8	>= 1 - < 5 %


### California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, Cumene, Benzene, Trimethyl phosphate, Ethyl Acrylate, which is/are known to the State of California to cause cancer, and Benzene, Sulfur dioxide, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



Revision Date : 03/29/2023

# SAFETY DATA SHEET



## MOTOR MEDIC® TRANSEAL® AUTOMATIC TRANSMISSION SEALER

Version	Revision Date:	SDS Number:	Date of last issue: 05/27/2020
1.1	03/29/2023	600000001820	Date of first issue: 05/27/2020

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN