

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

SECTION 1. IDENTIFICATION

Product name : MM BEARIN' SEAL ENGINE SEALER 12/12 OZ
Product code : M1616

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : SEALER
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :

Signal word : Danger

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Hazard statements : Combustible liquid.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.

Precautionary statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards
None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL
STOP LEAK**

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-54-7	>= 50 - < 70
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 20 - < 30
tert-Butylbenzene	98-06-6	>= 10 - < 20
p-Diethylbenzene	105-05-5	>= 1 - < 5
1,2,3,5-tetramethylbenzene	527-53-7	>= 1 - < 5
1,2,3,4-tetramethylbenzene	488-23-3	>= 1 - < 5
Naphthalene	91-20-3	>= 1 - < 5
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5
1,2,3-Trimethylbenzene	526-73-8	>= 1 - < 5
Linseed Oil	8001-26-1	>= 1 - < 5
Diethylbenzene	25340-17-4	>= 1 - < 5
Cumene	98-82-8	>= 1 - < 5
Benzene, 1,3-diethyl-	141-93-5	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
- Notes to physician : Treat symptomatically.

MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 02/15/2022
1.2	03/29/2023	600000001821	Date of first issue: 07/17/2019

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap-

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-54-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Solvent naphtha (petroleum), heavy arom.	64742-94-5	TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
Naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m ³	NIOSH REL
		ST	15 ppm 75 mg/m ³	NIOSH REL
		TWA	10 ppm 50 mg/m ³	OSHA Z-1
		TWA	10 ppm 50 mg/m ³	OSHA P0
		STEL	15 ppm 75 mg/m ³	OSHA P0
		1,2,4-Trimethylbenzene	95-63-6	TWA
1,2,3-Trimethylbenzene	526-73-8	TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m ³	OSHA P0
		TWA	25 ppm 125 mg/m ³	NIOSH REL
		TWA	25 ppm	ACGIH

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

		TWA	25 ppm 125 mg/m3	OSHA P0
Linseed Oil	8001-26-1	TWA (mist - total)	10 mg/m3	NIOSH REL
		TWA (mist - respirable)	5 mg/m3	NIOSH REL
Diethylbenzene	25340-17-4	TWA	5 ppm	US WEEL
Cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : not determined

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : ≥ 179 °C
Value for Component

Flash point : 61 °C
Method: closed cup
Value for Component

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Evaporation rate : not determined

Flammability (solid, gas) : No data available

Self-ignition : not determined

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

Vapour pressure : not determined

Relative vapour density : not determined

Density : 0.8645 g/cm³

Solubility(ies)
Water solubility : negligible

Partition coefficient: n-octanol/water : not determined

Decomposition temperature : not determined

Viscosity
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents
Not applicable

Hazardous decomposition products : Carbon oxides

**MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL
STOP LEAK**

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Distillates (petroleum):**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Solvent naphtha (petroleum), heavy arom.:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

tert-Butylbenzene:

Acute oral toxicity : LD50 (Rat): 3,503 mg/kg

1,2,3,5-tetramethylbenzene:

Acute oral toxicity : LD50 (Rat): 5,157 mg/kg

Naphthalene:

Acute oral toxicity : LD50 (Mouse, male): 533 mg/kg

**MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL
STOP LEAK**

Version	Revision Date:	SDS Number:	Date of last issue: 02/15/2022
1.2	03/29/2023	600000001821	Date of first issue: 07/17/2019

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,500 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

1,2,4-Trimethylbenzene:

Acute oral toxicity : LD50 (Rat): 6 g/kg

Acute inhalation toxicity : LC50 (Rat): 10.2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,440 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.
Remarks: Information given is based on data obtained from similar substances.

1,2,3-Trimethylbenzene:

Acute oral toxicity : LD50 (Rat): 6 g/kg

Acute inhalation toxicity : LC50 (Rat): > 10,200 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,440 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Diethylbenzene:

Acute oral toxicity : LD50 (Rat, male and female): 2,050 mg/kg

Acute inhalation toxicity : LC50 (Rat, male): > 2100 ppm
Exposure time: 7 h
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit, male and female): > 5,000 mg/kg

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Cumene:

Acute oral toxicity : LD50 (Rat): 2,910 mg/kg
Acute inhalation toxicity : LC50 (Rat): 8000 ppm
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Distillates (petroleum):

Result: Possibly irritating to skin

Solvent naphtha (petroleum), heavy arom.:

Result: Repeated exposure may cause skin dryness or cracking.

tert-Butylbenzene:

Result: Irritating to skin.

p-Diethylbenzene:

Result: Possibly irritating to skin

1,2,3,5-tetramethylbenzene:

Result: Irritating to skin.

1,2,3,4-tetramethylbenzene:

Result: Irritating to skin.

Naphthalene:

Result: Possibly irritating to skin

1,2,4-Trimethylbenzene:

Result: Irritating to skin.

1,2,3-Trimethylbenzene:

Result: Irritating to skin.

Diethylbenzene:

Species: Rabbit
Assessment: Irritating to skin.

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 02/15/2022
1.2	03/29/2023	600000001821	Date of first issue: 07/17/2019

Method: OECD Test Guideline 404
Result: Irritating to skin.
GLP: yes

Cumene:

Result: No skin irritation

Benzene, 1,3-diethyl-:

Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: May cause irreversible eye damage.

Components:

Distillates (petroleum):

Result: No eye irritation
Assessment: No eye irritation

Solvent naphtha (petroleum), heavy arom.:

Result: Possibly irritating to eyes

tert-Butylbenzene:

Result: Irritating to eyes.

p-Diethylbenzene:

Result: Irritating to eyes.

1,2,3,5-tetramethylbenzene:

Result: Irritating to eyes.

1,2,3,4-tetramethylbenzene:

Result: Irritating to eyes.

Naphthalene:

Result: Possibly irritating to eyes

1,2,4-Trimethylbenzene:

Result: Irritating to eyes.

1,2,3-Trimethylbenzene:

Result: Irritating to eyes.

**MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL
STOP LEAK**

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Diethylbenzene:

Species: Rabbit
Result: Possibly irritating to eyes
GLP: yes

Cumene:

Result: No eye irritation

Benzene, 1,3-diethyl-:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Solvent naphtha (petroleum), heavy arom.:

Result: Not a skin sensitizer.

1,2,4-Trimethylbenzene:

Species: Guinea pig
Result: Did not cause sensitisation on laboratory animals.
Remarks: Information given is based on data obtained from similar substances.

1,2,3-Trimethylbenzene:

Species: Guinea pig
Result: Did not cause sensitisation on laboratory animals.
Remarks: Information given is based on data obtained from similar substances.

Diethylbenzene:

Test Type: Buehler Test
Species: Guinea pig
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406
Result: Did not cause sensitisation on laboratory animals.
GLP: yes

Cumene:

Test Type: Maximisation Test
Species: Guinea pig
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406

**MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL
STOP LEAK**

Version	Revision Date:	SDS Number:	Date of last issue: 02/15/2022
1.2	03/29/2023	600000001821	Date of first issue: 07/17/2019

Germ cell mutagenicity

Not classified based on available information.

Components:**1,2,4-Trimethylbenzene:**

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

1,2,3-Trimethylbenzene:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Method: OECD Test Guideline 474
Result: negative

Diethylbenzene:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male and female)
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Cumene:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Mouse
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**Solvent naphtha (petroleum), heavy arom.:**

Carcinogenicity - Assessment : Suspected human carcinogens

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Naphthalene:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Cumene:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC

Group 2B: Possibly carcinogenic to humans

Naphthalene 91-20-3

Cumene 98-82-8

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Reasonably anticipated to be a human carcinogen

Naphthalene 91-20-3

Cumene 98-82-8

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Solvent naphtha (petroleum), heavy arom.:

Assessment: May cause drowsiness or dizziness.

1,2,3,4-tetramethylbenzene:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

1,2,4-Trimethylbenzene:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

1,2,3-Trimethylbenzene:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

Cumene:

Exposure routes: Inhalation

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 02/15/2022
1.2	03/29/2023	600000001821	Date of first issue: 07/17/2019

Target Organs: Upper respiratory tract
Assessment: May cause respiratory irritation.

Benzene, 1,3-diethyl-:

Exposure routes: Inhalation
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum), heavy arom.:

May be fatal if swallowed and enters airways.

1,2,4-Trimethylbenzene:

May be fatal if swallowed and enters airways.

1,2,3-Trimethylbenzene:

May be fatal if swallowed and enters airways.

Diethylbenzene:

May be fatal if swallowed and enters airways.

Cumene:

May be fatal if swallowed and enters airways.

Benzene, 1,3-diethyl-:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

SAFETY DATA SHEET



MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Naphthalene	91-20-3	100	4383
Benzene	71-43-2	10	10 (D018)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Carcinogenicity
Aspiration hazard
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Naphthalene	91-20-3	>= 1 - < 5 %
1,2,4-Trimethylbenzene	95-63-6	>= 1 - < 5 %
Cumene	98-82-8	>= 1 - < 5 %

California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SAFETY DATA SHEET




MOTOR MEDIC® BEARIN' SEAL® ENGINE OIL STOP LEAK

Version 1.2 Revision Date: 03/29/2023 SDS Number: 600000001821 Date of last issue: 02/15/2022
Date of first issue: 07/17/2019

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 03/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN