

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

SECTION 1. IDENTIFICATION

Product name : MM SYN MOTOR FLUSH 12/32 OZ
Product code : MFD1

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : ENGINE FLUSH
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 4
Eye irritation : Category 2A
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : Combustible liquid.
May be fatal if swallowed and enters airways.
Causes serious eye irritation.

Precautionary statements : **Prevention:**
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version	Revision Date:	SDS Number:	Date of last issue: 02/17/2022
1.3	03/29/2023	600000001746	Date of first issue: 02/21/2019

Wash skin thoroughly after handling.
Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.

Do NOT induce vomiting.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-54-7	>= 50 - < 70
Diethylene glycol monobutyl ether	112-34-5	>= 5 - < 10
Distillates (petroleum)	64742-53-6	>= 1 - < 5
Zinc dialkyl dithiophosphate	68649-42-3	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.

MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3	Revision Date: 03/29/2023	SDS Number: 600000001746	Date of last issue: 02/17/2022 Date of first issue: 02/21/2019
----------------	------------------------------	-----------------------------	---

- Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes serious eye irritation.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO2)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Diethylene glycol monobutyl ether	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Distillates (petroleum)	64742-53-6	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version	Revision Date:	SDS Number:	Date of last issue: 02/17/2022
1.3	03/29/2023	600000001746	Date of first issue: 02/21/2019

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: not determined
Odour	: not determined
Odour Threshold	: not determined
pH	: not determined
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: 85 °C Value for Component
Evaporation rate	: not determined
Flammability (solid, gas)	: No data available
Self-ignition	: not determined
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapour pressure	: not determined
Relative vapour density	: not determined
Density	: 0.8671 g/cm ³

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

Solubility(ies)
Water solubility : not determined

Partition coefficient: n-octanol/water : not determined

Decomposition temperature : not determined

Viscosity
Viscosity, dynamic : not determined
Viscosity, kinematic : not determined

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Distillates (petroleum):

Acute oral toxicity : LD50 (Rat): > 15 g/kg

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Diethylene glycol monobutyl ether:

Acute oral toxicity : LD50 (Rat): 3,305 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,734 mg/kg

Distillates (petroleum):

Acute oral toxicity : LD50 (Rat): > 5 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Distillates (petroleum):

Result: Possibly irritating to skin

Diethylene glycol monobutyl ether:

Result: Possibly irritating to skin

Distillates (petroleum):

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: May cause irreversible eye damage.

Components:

Distillates (petroleum):

Result: No eye irritation
Assessment: No eye irritation

Diethylene glycol monobutyl ether:

Result: Irritating to eyes.

Distillates (petroleum):

Result: No eye irritation

MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version	Revision Date:	SDS Number:	Date of last issue: 02/17/2022
1.3	03/29/2023	600000001746	Date of first issue: 02/21/2019

Zinc dialkyl dithiophosphate:

Result: Corrosive

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Diethylene glycol monobutyl ether:**

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Distillates (petroleum):

Result: Not a skin sensitizer.

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.

Components:**Diethylene glycol monobutyl ether:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Result: In vivo tests did not show mutagenic effects

Carcinogenicity

Not classified based on available information.

Components:**Distillates (petroleum):**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen., Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

Reproductive toxicity

Not classified based on available information.

Components:

Diethylene glycol monobutyl ether:

Effects on foetal development : Remarks: No teratogenic effects

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Diethylene glycol monobutyl ether:

NOAEL: 250 mg/kg
LOAEL: 1,000 mg/kg
Application Route: Oral
Target Organs: Blood

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Lead	7439-92-1	10	10 (D008)
Lead	7439-92-1	10	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Aspiration hazard
Serious eye damage or eye irritation

SAFETY DATA SHEET



MOTOR MEDIC® SYNTHETIC MOTOR FLUSH

Version 1.3 Revision Date: 03/29/2023 SDS Number: 600000001746 Date of last issue: 02/17/2022
Date of first issue: 02/21/2019

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Diethylene glycol mono-butyl ether	112-34-5	>= 5 - < 10 %
Zinc dialkyl dithiophosphate	68649-42-3	>= 1 - < 5 %
2-Butoxyethanol	111-76-2	>= 0.1 - < 1 %


California Prop. 65

WARNING: This product can expose you to chemicals including 1,4-Dioxane, Lead, Propylene Oxide, Ethylene Oxide, Arsenic, Cadmium, which is/are known to the State of California to cause cancer, and Lead, Methanol, Ethylene Oxide, Cadmium, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 03/29/2023
Reason for change : Raw Material Change

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN