Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

29 CFR 1910.1200 (OSHA HazCom 2012)

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	, , , , , , , , , , , , , , , , , , ,
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-8326-825)
United States of America (USA)	, , ,
1-800-TEAMVAL (1-800-8326-825)	Product Information
,	1-800-TEAMVAL (1-800-8326-825)
	, , , , , , , , , , , , , , , , , , , ,

# **SECTION 2. HAZARDS IDENTIFICATION**

## **GHS Classification**

This material is considered hazardous under the OSHA Hazard Communication Standard criteria, based on hazard(s) not otherwise classified.

# **GHS** label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

## Other hazards

Static-accumulating flammable liquid.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

# **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	18.3634
Lubricating oils (petroleum), hydrotreated	64742-58-1	This material is considered hazardous under the OSHA Hazard	2.0849

<b>Valvoline</b>	Page: 2
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

	Communication Standard criteria, based on hazard(s) not otherwise classified.	
--	---	--

## **SECTION 4. FIRST AID MEASURES**

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

abnormalities.

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

•

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
Distillates (Petroleum),	64742-54-7	TWA	5 mg/m3	OSHA Z-1
Hydrotreated Heavy Paraffinic			Mist	
		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL
			Mist	
		PEL	5 mg/m3	CAL PEL
			particulate	
Lubricating oils (petroleum),	64742-58-1	TWA	5 mg/m3	ACGIH
hydrotreated			Inhalable fraction	

**Engineering measures** : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point :  $> 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$ 

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids)

Flammability (liquids) : Static-accumulating flammable liquid.

Upper explosion limit : 6 %(V)

Calculated Explosive Limit

Lower explosion limit : 1 %(V)

Vapour pressure Calculated Explosive Limit
Calculated Explosive Limit
Color 0.0133333 hPa (21.11 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.868 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 102 mm2/s (40 °C)

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

Oxidizing properties : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Hydrocarbons

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Inhalation

exposure

: Inhalation Skin contact

Eye Contact Ingestion

#### Acute toxicity

Not classified based on available information.

#### **Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Lubricating oils (petroleum), hydrotreated:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

#### Skin corrosion/irritation

Not classified based on available information.

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

# **Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

Lubricating oils (petroleum), hydrotreated:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Result: Slight, transient irritation

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

## Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

Lubricating oils (petroleum), hydrotreated:

Result: Slight, transient irritation

# Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

## STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Product:**

No aspiration toxicity classification

# **Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

### **Further information**

#### **Product:**

Remarks: No data available

# Carcinogenicity:

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

**IARC** No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

**NTP** No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

## **Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

# Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Toxicity to fish : LL50 (Fish): > 100 mg/l

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other : LC50 (Brine shrimp (Artemia salina)): > 22,500 mg/l

aquatic invertebrates Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility

#### Persistence and degradability

## Components:

No data available

Bioaccumulative potential

**Components:** 

<b>Valvoline</b>	Page: 9
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

No data available

Mobility in soil

**Components:** 

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: No data available

# **Components:**

# **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

# **SECTION 14. TRANSPORT INFORMATION**

# International transport regulations

## **REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

# **U.S. DOT - ROAD**

Not dangerous goods	

# CFR\_RAIL\_C

Not dangerous goods	

# **U.S. DOT - INLAND WATERWAYS**

<u> </u>	INE WATERWAY
	Not dangerous goods

# TDG\_ROAD\_C

Not dangerous goods

#### TDG RAIL C

 IDO_INAIL_O		
Not	dangerous goods	

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

TDG	INWT	C

Not dangerous goods

#### INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

## INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

## **INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

#### MX DG

Not dangerous goods

### \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity**

Components	CAS-No. Component RQ		Calculated product RQ
		(lbs)	(lbs)
TOLUENE	108-88-3	1000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
SULFUR DIOXIDE	7446-09-5	500	*
SULFUR DIOXIDE	7446-09-5		*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

California Prop 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth defects, or other

reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Contact your sales representative for additional information.

KECI : On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)

PICCS : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**

# **Further information**

Revision Date: 07/10/2017



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

<b>Valvoline</b>	Page: 12
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 11/2/2017
	SDS Number: R0355879
MaxLife™ SAE 10W-40 HIGH MILEAGE MOTOR OIL	Version: 1.7
797977	

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System