

**SAFETY DATA SHEET**

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**Trade name : Valvoline™ VR1 Racing™ SAE 50
Racing Oil**Details of the supplier of the safety data sheet**Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-8326-825)**Emergency telephone number**

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-8326-825)

Product Information

1-800-TEAMVAL (1-800-8326-825)

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.


SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	5.6983
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	1.1397

SECTION 4. FIRST AID MEASURES

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/13/2017
		Print Date: 10/29/2018
		SDS Number: R0169797
Valvoline™ VR1 Racing™ SAE 50 Racing Oil		Version: 1.3
VV235		

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray

**SAFETY DATA SHEET**

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
nitrogen oxides (NO_x)

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

SAFETY DATA SHEET

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
Mineral Oil	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

SAFETY DATA SHEET

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 600.01 °F / 315.56 °C
 (1,013.333333 hPa)
 Calculated Phase Transition Liquid/Gas

Flash point : > 390 °F / > 199 °C
 Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 7 %(V)
 GLP: Calculated Explosive Limit

Lower explosion limit : 0.9 %(V)
 GLP: Calculated Explosive Limit

Vapour pressure : 0.1 hPa (20 °C)
 Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.8901 g/cm3 (15.56 °C)

Solubility(ies)
 Water solubility : No data available

Solubility in other solvents : No data available

**SAFETY DATA SHEET**

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

Partition coefficient: n-octanol/water : No data available

Thermal decomposition :
No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NO_x)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion


Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:
Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/13/2017
		Print Date: 10/29/2018
		SDS Number: R0169797
Valvoline™ VR1 Racing™ SAE 50 Racing Oil		Version: 1.3
VV235		

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Mineral Oil:

May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or

SAFETY DATA SHEET

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with



SAFETY DATA SHEET

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 07/13/2017

Print Date: 10/29/2018

SDS Number: R0169797

Valvoline™ VR1 Racing™ SAE 50 Racing Oil

Version: 1.3

VV235

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ZINC	7440-66-6	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)bis(phosphorodithioate)	2215-35-2	0.61 %
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	0.48 %
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8	0.36 %

SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/29/2018
	SDS Number: R0169797
Valvoline™ VR1 Racing™ SAE 50 Racing Oil VV235	Version: 1.3

California Prop 65 This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : Contact your sales representative for additional information.
- KECI : On the inventory, or in compliance with the inventory
- IECSC : q (quantity restricted)
- PICCS : Not in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 07/13/2017

<p>NFPA:</p>  <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/13/2017
		Print Date: 10/29/2018
		SDS Number: R0169797
Valvoline™ VR1 Racing™ SAE 50 Racing Oil		Version: 1.3
VV235		

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity


TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

	Page: 13
SAFETY DATA SHEET	Revision Date: 07/13/2017
	Print Date: 10/29/2018
	SDS Number: R0169797
Valvoline™ VR1 Racing™ SAE 50 Racing Oil VV235	Version: 1.3

DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System