



**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

---

**SECTION 1. IDENTIFICATION**

Product name : Valvoline™ Durablend™ SYNTHETIC BLEND SAE 5W-30  
Motor Oil

Product code : VV291

**Manufacturer or supplier's details**

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone : +1-800-VALVOLINE (+1-800-825-8654)  
number

---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Not a hazardous substance or mixture.

**GHS label elements**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1	>= 80 - < 90
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 5 - < 10

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.  
  
Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

- Hazardous combustion products : carbon dioxide and carbon monoxide
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.



**SAFETY DATA SHEET**  
 Valvoline™ Durablend™ SYNTHETIC BLEND  
 SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Inhalable particulate)	5 mg/m3	ACGIH



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

		matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

**Personal protective equipment**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Safety glasses
- Skin and body protection : Protective suit
- Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Colour : amber
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 424.9 °F / 218.3 °C
- Flash point : 433 °F / 223 °C



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

Method: Cleveland open cup

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	0.0133333 hPa (70.00 °F / 21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0.857
Density	:	0.850 g/cm3
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 3,400.000 mPa.s (-13 °F / -25 °C)
Viscosity, kinematic	:	59.5 mm2/s (104 °F / 40 °C)
Oxidizing properties	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

---

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit  
Result : No skin irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation



**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit  
Result : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

May be fatal if swallowed and enters airways.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**





**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l  
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

**Ecotoxicology Assessment**

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

- Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l
- Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

aquatic invertebrates  
(Chronic toxicity)

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Persistence and degradability**

**Components:**

**LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Bioaccumulative potential**

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Partition coefficient: n- : log Pow: Expected > 7  
octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological : No data available  
information



**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards



**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations**

**Massachusetts Right To Know**

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED 72623-87-1

**Pennsylvania Right To Know**

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED 72623-87-1

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7

PROPRIETARY SUBSTANCE OF OLOA 55603 - 0-276105 Not Assigned

HIGHLY REFINED MINERAL OIL (C15 - C50) Not Assigned

**Maine Chemicals of High Concern**

Product does not contain any listed chemicals

**Vermont Chemicals of High Concern**

Product does not contain any listed chemicals

**Washington Chemicals of High Concern**

Product does not contain any listed chemicals

**California Permissible Exposure Limits for Chemical Contaminants**

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED 72623-87-1

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY 64742-54-7



**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

---

PARAFFINIC

**The components of this product are reported in the following inventories:**

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	Not in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

---

**SECTION 16. OTHER INFORMATION**

**Further information**



**Valvoline™**  
**Global**


**SAFETY DATA SHEET**  
Valvoline™ Durablend™ SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	/	<b>1</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and



**Valvoline**<sup>™</sup>  
**Global**

**SAFETY DATA SHEET**  
Valvoline<sup>™</sup> Durablend<sup>™</sup> SYNTHETIC BLEND  
SAE 5W-30 Motor Oil

Version: 3.0

Revision Date: 06/19/2023

Print Date:  
06/21/2023

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/19/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0289367