

Page: 1

SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease	Version: 1.3
[™] Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV614	

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease

[™] Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL
United States of America (USA)	
1-800-TEAMVAL	Product Information
	1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	74.9999
ASPHALT		This material is not considered hazardous under the OSHA Hazard	24.9999



SAFETY DATA SHEET	Revision Date: 05/19/201
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries	Version: 1.3
VV614	

		Communication Standard (HazCom 2012).	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	9.9999

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
		Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various	Version: 1.3
countries	
VV614	

the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	Use extinguishing measures that are appropriate to circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical	local
Specific hazards during firefighting	Do not allow run-off from fire fighting to enter drains courses.	or water
Hazardous combustion products	carbon dioxide and carbon monoxide Sulphur oxides Hydrocarbons Aldehydes Ketones Nitrogen oxides (NOx)	
Specific extinguishing methods		
	Product is compatible with standard fire-fighting age	ents.
Further information	Standard procedure for chemical fires.	
Special protective equipment for firefighters	In the event of fire, wear self-contained breathing ap	oparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease	Version: 1.3
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
\/\/614	

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ASPHALT	8052-42-4	TWA	0.5 mg/m3 Fume, inhalable fraction (benzene soluble aerosol)	ACGIH
		С	5 mg/m3 Fumes	NIOSH REL
		PEL	5 mg/m3 Fumes	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components		CAS-No.
DISTILLATES (P	ETROLEUM),	64742-65-0
SOLVENT-DEW		
PARAFFINIC		



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease	Version: 1.3
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV614	

Engineering measures :	General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Personal protective equipment	
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye protection :	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection :	Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures :	General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	gel
Physical state	:	liquid
Colour	:	red
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	640 °F / 338 °C
Flash point	:	471 °F / 244 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available



SAFETY DATA SHEET	Revision Date: 05/19/201
	Print Date: 10/29/201
	SDS Number: R017217
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries	Version: 1.
VV614	

Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: < 0.01 mmHg (20 °C)
Relative vapour density	: No data available
Relative density	: 0.95 (15.6 °C)
Density	: 0.90 g/cm3 (20 °C)
Solubility(ies) Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: > 315 °C
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: None known.
Incompatible materials	: Strong oxidizing agents



Page: 7

SAFETY DATA SHEETRevision Date: 05/19/2017Print Date: 10/29/2018Print Date: 10/29/2018SDS Number: R0172170Valvoline™ Multi-Vehicle Multi-Purpose Red Grease™ Trademark, Valvoline or its subsidiaries, registered in various
countries
VV614

products

carbon dioxide and carbon monoxide Hydrocarbons Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion
Acute toxicity Not classified based on availab	le information.
<u>Product:</u> Acute oral toxicity	: Acute toxicity estimate (Rat): 3,019 mg/kg
Acute dermal toxicity	: Acute toxicity estimate (Rabbit): 169,492 mg/kg
<u>Components:</u> DISTILLATES (PETROLEUM), Acute oral toxicity	SOLVENT-DEWAXED HEAVY PARAFFINIC: : LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg
ASPHALT: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	 Assessment: Not classified as acutely toxic by inhalation under GHS. Remarks: Information given is based on data obtained from similar substances.
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS.
DISTILLATES (PETROLEUM), Acute oral toxicity	HYDROTREATED HEAVY NAPHT: : LD50 (Rat): > 5 g/kg
Acute inhalation toxicity	 LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: Not classified as acutely toxic by inhalation under GHS.



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various	Version: 1.3
countries VV614	

Acute dermal toxicity

: LD50 (Rabbit): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose.

Skin corrosion/irritation Not classified based on available information. Product: Result: No skin irritation

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Slight, transient irritation

ASPHALT: Species: Rabbit Result: No skin irritation Remarks: Information given is based on data obtained from similar substances.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT: Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information. **Product:** Result: No eye irritation

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Slight, transient irritation

ASPHALT: Species: Rabbit Remarks: May irritate eyes.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT: Species: Rabbit Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Components: ASPHALT: Test Type: Buehler Test



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease	Version: 1.3
[™] Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV614	

Species: Guinea pig Assessment: Does not cause skin sensitisation.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT: Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406

Germ cell mutagenicity Not classified based on available information. <u>Components:</u> ASPHALT: Genotoxicity in vitro : Result: Positi

: Result: Positive results were obtained in some in vitro tests.

Carcinogenicity

Not classified based on available information. **Reproductive toxicity** Not classified based on available information. **STOT - single exposure** Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. **Product:** No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: May be fatal if swallowed and enters airways.

Further information Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.
<u>Components:</u> ASPHALT: Toxicity to fish	: Remarks: No toxicity at the limit of solubility QSAR



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries VV614	Version: 1.3

Toxicity to daphnia and other aquatic invertebrates	: Remarks: No toxicity at the limit of solubility QSAR
Toxicity to algae	: Remarks: No toxicity at the limit of solubility QSAR
Toxicity to fish (Chronic toxicity)	: Remarks: No toxicity at the limit of solubility QSAR
DISTILLATES (PETROLEUM), Toxicity to fish	 HYDROTREATED HEAVY NAPHT: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	 EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	 NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	 NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211
Persistence and degradability	/
ASPHALT: Biodegradability	: Result: Not readily biodegradable.
DISTILLATES (PETROLEUM), Biodegradability	 HYDROTREATED HEAVY NAPHT: Result: Inherently biodegradable. Biodegradation: 31 % Exposure time: 28 d Method: OECD Test Guideline 301F
No data available Bioaccumulative potential No data available	



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease	Version: 1.3
™ Trademark, Valvoline or its subsidiaries, registered in various	
countries	
VV614	

Mobility in soilNo data availableOther adverse effectsNo data availableProduct:Additional ecological: No data availableinformation

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal r	nethods
------------	---------

General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries VV614	Version: 1.3

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity This material does not contain any components with a CERCLA RQ. SARA 304 Extremely Hazardous Substances Reportable Quantity This material does not contain any components with a section 304 EHS RQ.	
SARA 311/312 Hazards	No SARA Hazards
SARA 313	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65	Proposition 65 warnings are not required for this product based on the results of a risk assessment.
• •	ct are reported in the following inventories: On TSCA Inventory
AICS	On the inventory, or in compliance with the inventory



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries VV614	Version: 1.3

DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/19/2017



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

Page: 14



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries	Version: 1.3
VV614	

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association



SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 10/29/2018
	SDS Number: R0172170
Valvoline [™] Multi-Vehicle Multi-Purpose Red Grease [™] Trademark, Valvoline or its subsidiaries, registered in various countries VV614	Version: 1.3

NIOSH : National Institute for Occupational Safety and Health OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System