



SAFETY DATA SHEET	Revision Date: 12/26/201
	Print Date: 10/29/201
	SDS Number: 0000009160
No data. VV70518	Version: 1.

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

No data available

Relevant identified uses of the substance or mixture and uses advised against Recommended use : Lubricant

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	
1-800-TEAMVAL (1-800-832-6825)	Product Information
, , , , , , , , , , , , , , , , , , ,	1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Reproductive toxicity	Category 2
GHS label elements Hazard pictograms	
Signal Word	Warning
Hazard Statements	Suspected of damaging fertility or the unborn child.
Precautionary Statements	 Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF exposed or concerned: Get medical advice/ attention. Storage: Store locked up. Disposal: Dispose of contents/ container to an approved waste disposal plant.



SAFETY DATA SHEET

Revision Date: 12/26/2017

S

SDS Number: 00000091604 Version: 1.7

Print Date: 10/29/2018

Other hazards

None known.

No data. VV70518

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
		1111/1010

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	50.2739
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT)	64742-65-0	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	6.0393
ZINC BIS[O-(6- METHYLHELPTYL)]BIS[O-SEC- BUTYL)]BIS(DITHIOPHOSPATE)	93819-94-4	Skin Irrit. 2; H315 Eye Dam. 1; H318	1.0871
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA	64741-89-5	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	1.0065
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7	Not a hazardous substance or mixture.	1.0065
Dodecylphenol, mixed isomers (branched)	74499-35-7	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361	0.2012

SECTION 4. FIRST AID MEASURES



Revision Date: 12/26/2017

	Print Date: 10/29/2018
	SDS Number: 00000091604
No data.	Version: 1.7
VV70518	

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	:	Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Suspected of damaging fertility or the unborn child. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Notes to physician	:	No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



....

SAFETY DATA SHEET

Revision Date: 12/26/2017

• • • • • • • • • • • • • • • • • • • •	
	Print Date: 10/29/2018
	SDS Number: 000000091604
No data.	Version: 1.7
VV70518	

		Water spray Foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide Hydrocarbons nitrogen oxides (NOx) zinc oxide Sulphur oxides hydrogen sulfide mercaptans Aldehydes
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	:	Comply with all applicable federal, state, and local regulations.





Revision Date: 12/26/2017

Print Date: 10/29/2018 SDS Number: 00000091604

Version: 1.7

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

No data. VV70518

Advice on safe handling	 Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	 Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
Distillates (Petroleum),	64742-54-7	TWA	5 mg/m3	OSHA Z-1
Hydrotreated Heavy Paraffinic			Mist	
		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL
			Mist	
		PEL	5 mg/m3	CAL PEL
			particulate	
DISTILLATES (PETROLEUM),	64742-65-0	TWA	5 mg/m3	OSHA Z-1
SOLVENT-DEWAXED HEAVY			Mist	
PARAFFINIC (<3 % DMSO				
EXTRACT)				
		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL

SAFETY DATA SHEET	Revision Date: 12/26/2017
	Print Date: 10/29/2018
	SDS Number: 00000091604
No data.	Version: 1.7
VV70518	

1			Mist	
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA	64741-89-5	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
ZINC BIS[O-(6-	93819-94-4
METHYLHELPTYL)]BIS[O-	
SEC-	
BUTYL)]BIS(DITHIOPHOSPAT	
E)	
Dodecylphenol, mixed isomers	74499-35-7
(branched)	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has



SAFETY DATA SHEET Revision Date: 12/26/2017 Print Date: 10/29/2018 SDS Number: 00000091604 No data. Version: 1.7 VV70518 Version: 1.7

		otherwise been determined. Protection provided by air- purifying respirators is limited. Use a positive pressure, air- supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.
Hand protection		
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	:	Wear resistant gloves (consult your safety equipment supplier). Wear as appropriate: Impervious clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
	No data available
Boiling point/boiling range	: 392 °F / 200 °C Coloulated Phase Transition Liquid/Con
Flash point	Calculated Phase Transition Liquid/Gas : > 390 °F / > 199 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V)



Page: 8

Revision Date: 12/26/2017

 Print Date: 10/29/2018

 SDS Number: 00000091604

 No data.

 VV70518

GLP: Calculated Explosive Limit

Lower explosion limit	: 1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 1.33333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.8556 (20 °C)
Density	: No data available
Solubility(ies) Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: 100 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Acids Strong oxidizing agents
	Strong oxidizing agents
Hazardous decomposition products	Aldehydes



Revision Date: 12/26/2017

No data. VV70518

Print Date: 10/29/2018 SDS Number: 00000091604

Version: 1.7

carbon dioxide and carbon monoxide Hydrocarbons hydrogen sulfide Nitrogen oxides (NOx) Sulphur oxides zinc oxide fumes mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion
Acute toxicity Not classified based on availab <u>Components:</u> Distillates (Petroleum), Hydrotr Acute oral toxicity	
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
DISTILLATES (PETROLEUM) EXTRACT): Acute oral toxicity	SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO : LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg
	TYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE): : LD50 (Rat): 2,600 mg/kg
Acute dermal toxicity	 LD50 (Rabbit): > 3,160 mg/kg Method: OECD Test Guideline 402 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
	SOLVENT-REFINED LIGHT PA: : LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
CATALYTIC DE WAXED HEA Acute oral toxicity	 VY PARAFFINIC OIL (PETROLEUM): LD50 (Rat): > 2,000 mg/kg Assessment: Not classified as acutely toxic by ingestion under GHS.



Print Date: 10/29/2018

	SDS Number: 00000091604
No data.	Version: 1.7
VV70518	

Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg
	Assessment: Not classified as acutely toxic by dermal
	absorption under GHS.
	Remarks: Information given is based on data obtained from
	similar substances.

Skin corrosion/irritation

Not classified based on available information. <u>Components:</u> Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: Slight, transient irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT): Result: Slight, transient irritation

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE): Species: Guinea pig Method: OECD Test Guideline 404 Result: Irritating to skin. Remarks: Information given is based on data obtained from similar substances.

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA: Result: Slight, transient irritation

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM): Result: Slight, transient irritation

Dodecylphenol, mixed isomers (branched): Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT): Result: Slight, transient irritation

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE): Species: Rabbit Result: Corrosive Remarks: Information given is based on data obtained from similar substances.



Revision Date: 12/26/2017

Print Date: 10/29/2018 SDS Number: 00000091604

No data. VV70518 r: 000000091604 Version: 1.7

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PA: Result: Slight, transient irritation

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM): Result: Slight, transient irritation

Dodecylphenol, mixed isomers (branched): Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. **Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3 % DMSO EXTRACT):

Genotoxicity in vitro

: Test Type: Ames test Result: negative

'L)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):
Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
Remarks: Information given is based on data obtained from similar substances.
Test Type: Micronucleus test
Test species: Mouse
Method: OECD Test Guideline 474
Result: negative

similar substances.

Carcinogenicity

Not classified based on available information. **Reproductive toxicity** Suspected of damaging fertility or the unborn child. <u>Components:</u> Dodecylphenol, mixed isomers (branched): Reproductive toxicity - : Some evidence of Assessment fertility, and/or or

: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Remarks: Information given is based on data obtained from

STOT - single exposure

Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. <u>Product:</u>



SAFETY DATA SHEET	Revision Date: 12/26/2017
	Print Date: 10/29/2018
	SDS Number: 00000091604
No data. VV/70518	Version: 1.7

No aspiration toxicity classification

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

Further information Product:

Remarks: No data available

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity	: Acute aquatic toxicity Category 3; Harmful to aquatic life.
Chronic aquatic toxicity	: Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.
<u>Components:</u> Distillates (Petroleum), Hydroti Toxicity to fish	reated Heavy Paraffinic: : LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l



Revision Date: 12/26/2017

	/L)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE): LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Water flea (Daphnia magna)): 5.4 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae :	EC50 (Selenastrum capricornutum (green algae)): 2.1 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test
Dodecylphenol, mixed isomers (b	pranched):
Ecotoxicology Assessment Acute aquatic toxicity :	Very toxic to aquatic life.
Chronic aquatic toxicity :	Very toxic to aquatic life with long lasting effects.
	 /L)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE): Result: Not readily biodegradable. Biodegradation: 1.5 % Exposure time: 28 d Method: OECD Test Guideline 301B
	′L)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE): log Pow: 0.59 - 1.2 (23 °C)
	/ PARAFFINIC OIL (PETROLEUM): log Pow: > 3.5
No data available Mobility in soil <u>Components:</u> No data available Other adverse effects No data available <u>Product:</u> Additional ecological : information	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life
Components:	with long lasting effects.

Components:





SAFETY DATA SHEET	Revision Date: 12/26/2017
	Print Date: 10/29/2018
	SDS Number: 00000091604
No data. VV70518	Version: 1.7

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
General advice	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods



SAFETY DATA SHEET	Revision Date: 12/26/2017
	Print Date: 10/29/2018
	SDS Number: 00000091604
No data.	Version: 1.7
VV70518	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

no

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ETHYLENEDIAMINE	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ		
		(lbs)	(lbs)		
ETHYLENEDIAMINE	107-15-3	5000	*		

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Chronic Health Hazard

SARA 313

ZINC BIS[O-(6-93819-94-41.08 % METHYLHELPTYL)]BIS[O -SEC-BUTYL)]BIS(DITHIOPHOS PATE)



SAFETY DATA SHEET	Revision Date: 12/26/201
	Print Date: 10/29/20
	SDS Number: 0000009160
No data.	Version: 1
VV70518	

California Prop 65 The components of this produ	This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. ct are reported in the following inventories:
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 12/26/2017



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.



SAFETY DATA SHEET

	Print Date: 10/29/2018
	SDS Number: 00000091604
No data.	Version: 1.7
VV70518	

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative



Revision Date: 12/26/2017

Print Date: 10/29/2018 SDS Number: 000000091604

No data. VV70518 Version: 1.7

WEL : Workplace Exposure Level

SAFETY DATA SHEET

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association NIOSH : National Institute for Occupational Safety and Health OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System