		Page: 1
SAFETY DATA SHEET		Revision Date: 08/14/2017
		Print Date: 10/29/2018
		SDS Number: R0173402
Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID VV813		Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ UNITRAC HYDRAULIC FLD
HYDRAULIC FLUID

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825)</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-8326-825)</p> <p>Product Information 1-800-TEAMVAL (1-800-8326-825)</p>
--	---


SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	4.1255
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	2.4007
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Eye Irrit. 2A; H319	1.5041
PHOSPHORODITHIOIC ACID	4259-15-8	Eye Dam. 1; H318	1.5041
Lubricating oils (petroleum), hydrotreated	64742-58-1	This material is considered hazardous under the OSHA Hazard Communication Standard criteria, based on hazard(s) not otherwise classified.	1.4736
C14-C18 alpha-olefin epoxide, reaction products with boric acid		Skin Sens. 1; H317	0.4994
PHOSPHOROUS ACID, TRIPHENYL ESTER	101-02-0	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2A; H319	0.1023



SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Skin Sens. 1A; H317

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current



SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

workplace exposure limits is unlikely to cause pulmonary abnormalities.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons

Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Container hazardous when empty.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Distillates (Petroleum),	64742-54-7	TWA	5 mg/m3	OSHA Z-1

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Hydrotreated Heavy Paraffinic			Mist	
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Lubricating oils (petroleum), hydrotreated	64742-58-1	TWA	5 mg/m3 Inhalable fraction	ACGIH

Hazardous components without workplace control parameters

Components	CAS-No.
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS	
PHOSPHORODITHIOIC ACID	4259-15-8
C14-C18 alpha-olefin epoxide, reaction products with boric acid	
PHOSPHOROUS ACID, TRIPHENYL ESTER	101-02-0

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: amber
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: > 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.880 (15.6 °C)
Density	: 0.8711 g/cm ³
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available

**SAFETY DATA SHEET**

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : 9.55 mm²/s
Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : Stable under recommended storage conditions.
Possibility of hazardous reactions : Product will not undergo hazardous polymerization.
Conditions to avoid : excessive heat
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

PHOSPHORODITHIOIC ACID:Acute oral toxicity : LD50 (Rat): 3,100 mg/kg
Method: OECD Test Guideline 401Acute dermal toxicity : LD50 (Rabbit, male): > 5,000 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Lubricating oils (petroleum), hydrotreated:

 Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by ingestion under GHS.

 Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

PHOSPHOROUS ACID, TRIPHENYL ESTER:

 Acute oral toxicity : LD50 (Rat, male): 1.59 g/kg
 Method: OECD Test Guideline 401

 Acute inhalation toxicity : LC50 (Rat): > 6.7 mg/l
 Exposure time: 1 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

 Acute dermal toxicity : LD50 (Rabbit): > 2 - < 5 g/kg
 Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: No skin irritation

PHOSPHORODITHIOIC ACID:

Result: Slight, transient irritation

Lubricating oils (petroleum), hydrotreated:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Result: No skin irritation

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Species: Guinea pig

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Irritating to eyes.

PHOSPHORODITHIOIC ACID:

Result: Corrosive

Lubricating oils (petroleum), hydrotreated:

Result: Slight, transient irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Result: No eye irritation

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:**PHOSPHORODITHIOIC ACID:**

Result: Did not cause sensitisation on laboratory animals.

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Assessment: May cause sensitisation by skin contact.


PHOSPHOROUS ACID, TRIPHENYL ESTER:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

		Page: 11
SAFETY DATA SHEET		Revision Date: 08/14/2017
		Print Date: 10/29/2018
		SDS Number: R0173402
Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID		Version: 1.3
VV813		

Not classified based on available information.

Components:

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Genotoxicity in vitro : Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

PHOSPHORODITHIOIC ACID:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.4 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 75 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): 410 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other aquatic invertebrates : LC50 (Brine shrimp (Artemia salina)): > 22,500 mg/l
Exposure time: 48 h


Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

		Page: 13
SAFETY DATA SHEET		Revision Date: 08/14/2017
		Print Date: 10/29/2018
		SDS Number: R0173402
Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID		Version: 1.3
VV813		

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

PHOSPHORODITHIOIC ACID:

Biodegradability : Result: Not biodegradable
 Biodegradation: < 5 %
 Exposure time: 27 d
 Method: OECD Test Guideline 301D

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 84 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301D

No data available

Bioaccumulative potential

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Partition coefficient: n-octanol/water : log Pow: 6.62
 Remarks: QSAR

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.



SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402

Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO


Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

		Page: 15
SAFETY DATA SHEET		Revision Date: 08/14/2017
		Print Date: 10/29/2018
		SDS Number: R0173402
Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID		Version: 1.3
VV813		

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 313
PHOSPHORODITHIOIC ACID 4259-15-8 1.50 %

California Prop 65 This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

Revision Date: 08/14/2017

Print Date: 10/29/2018

SDS Number: R0173402


Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID

Version: 1.3

VV813

Further information

Revision Date: 08/14/2017

NFPA:	HMIS III:						
<p style="text-align: center;">Flammability</p>  <p style="text-align: center;">Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports


The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

		Page: 17
SAFETY DATA SHEET		Revision Date: 08/14/2017
		Print Date: 10/29/2018
		SDS Number: R0173402
Valvoline™ UNITRAC HYDRAULIC FLD HYDRAULIC FLUID		Version: 1.3
VV813		

CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System