

Transport Information Document

Date: May 18, 2016

3M ID Number: 60-9800-2290-3

Product Description: 3M(TM) Liquid Hardener, 05836, 22 cc Tube, 12 per case, Obsolete

Transport Protective Service: MAINTAIN TEMP BELOW 80F (27C)

NMFC Item: 043940	NMFC Sub: 00	NMFC Class: 085.0
		NMFC Class: 085.0
Flash Point (Closed-c	up): 200°F/93°C	
UNITED STATES DEPARTMENT OF TRANSPORTATION - GROUND (U.S. DOT, 49 CFR)		
LIMITED QUANTITY		
UNITED STATES DEPART	MENT OF TRANSPORTATION -	· VESSEL (U.S. DOT, 49 CFR)
UN3105, ORGANIC PEROX	(IDE TYPE D, LIQUID, (METHYL	ETHYL KETONE PEROXIDE<= 45%), 5.2, II, LIMITED QUANTITY
INTERNATIONAL AIR TRA	NSPORT ASSOCIATION (IATA)	
FORBIDDEN UN/ICAO PA	CKAGING NOT AVAILABLE	
INTERNATIONAL MARITIM	IE ORGANIZATION (IMO)	
UN3105, ORGANIC PEROX	(IDE TYPE D, LIQUID, (METHYL	ETHYL KETONE PEROXIDE<= 45%), 5.2, LIMITED QUANTITY

The classification is authorized by the Competent Authority of the United States of America and may not meet the requirements of other competent authorities.

These transportation classifications are provided as a customer service. AS THE SHIPPER YOU REMAIN RESPONSIBLE FOR COMPLYING WITH ALL THE APPLICABLE LAWS AND REGULATIONS, INCLUDING PROPER TRANSPORTATION CLASSIFICATION AND PACKAGING. 3M's transportation classifications are based on product formulations, packaging, 3M policies and 3M's understanding of applicable current regulations and is valid for the original 3M package only. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and NOT THE PACKAGING, LABELING, OR MARKING REQUIREMENTS. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.