

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/15/2014 : Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : JOHNSEN'S WINDSHIELD WASH CONCENTRATION 12 FL.OZ.

Product code : 2942

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Windshield Washer Concentrate

1.3. Details of the supplier of the safety data sheet

Technical Chemical Company P.O. BOX 139 Cleburne, Texas 76033 T 817-645-6088

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation:dust,mist) H331
STOT SE 1 H370
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02 GHS06

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs

Precautionary statements (GHS-US) : P210 - Keep away from heat,sparks,open flames,hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical, ventilating, lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P307+P311 - If exposed: Call a poison center/doctor

P311 - Call a poison center, doctor

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P321 - Specific treatment: See section 4.1 on SDS

P330 - Rinse mouth

P361 - Take off immediately all contaminated clothing P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: See Section 5.1 Extinguishing Media

04/11/2014 EN (English US) 1/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Methanol	(CAS No) 67-56-1	>= 95	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Polyethylene Glycol 200-600	(CAS No) 25322-68-3	<= 0.0045	Not classified
Nonyl Nonoxynol-5	(CAS No) 9014-93-1	<= 0.003	Not classified
Hydrogen [4-[4-(Diethylamino)-2',4'- Disulphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt	(CAS No) 129-17-9	~ 0.000001	Not classified

SECTION 4: First aid measures

First-aid measures after inhalation

4.1. Description of first aid measures

First-aid measures general : IF

: IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Call a POISON CENTER or doctor/physician.

: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a

POISON CENTER or doctor/physician.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.

Immediately call a POISON CENTER or doctor/physician. Wash with plenty of soap and water.

Wash contaminated clothing before reuse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water

for several minutes. Immediately call a POISON CENTER or doctor/physician. Obtain medical

attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a

POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: May damage fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation Symptoms/injuries after skin contact : Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.

: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.

Symptoms/injuries after eye contact

: Causes serious eye damage. Irritation of the eye tissue. Inflammation/damage of the eye tissue.

Symptoms/injuries after ingestion

Redness of the eye tissue.

Fatal if swallowed. Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

04/11/2014 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak,

cut off the supply.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Obtain special instructions . Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust,fume,gas,mist,vapor spray. Do not breathe

dust,fumes,gas,mist,vapor spray

Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking

or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical, ventilating, lighting

equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof

place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

04/11/2014 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods.

Personal protective equipment : Safety glasses. Gloves. Avoid all unnecessary exposure.





Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : Blue.

Odor : Mild . Odourless.
Odor threshold : 4.2 - 5960 ppm

pH : ≈ 7 Relative evaporation rate (butyl acetate=1) : 4.1

Melting point : No data available

Freezing point : -97.8

Boiling point : 64.7 °C

Flash point : 11 °C

Critical temperature : 239.4 °C

Auto-ignition temperature : 464 °C

Decomposition temperature : Not Determined
Flammability (solid, gas) : No data available
Vapor pressure : 12.8 kPa @ 20 deg C

Critical pressure : 77.77 bar

Relative vapor density at 20 °C : No data available

Relative density : 0.792

Solubility : Soluble in alcohols. Soluble in water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available

Explosive limits : 36.5 vol % Upper Explosive Limit (UEL)

9.2. Other information

VOC content : > 98 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

04/11/2014 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials

Strong acids. Strong bases.

Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

Information on toxicological effects

: Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. Acute toxicity

Polyethylene Glycol 200-600 (25322-68-3)	
LD50 oral rat	> 15000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)

Hydrogen [4-[4-(Diethylamino)-2',4'-Disulphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129-17-9)

LD50 oral rat 3001 mg/kg (Rat)

Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air

Skin corrosion/irritation : Not classified

pH: ≈ 7

Serious eye damage/irritation : Not classified

pH: ≈ 7

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified Based on available data, the classification criteria are not met

: Not classified Carcinogenicity

Hydrogen [4-[4-(Diethylamino)-2',4'-Disulphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129-17-9)

IARC group 3

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

Fatal if swallowed. Based on available data, the classification criteria are not met. Toxic if

swallowed. Toxic in contact with skin. Toxic if inhaled.

Symptoms/injuries after inhalation

Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/injuries after skin contact

Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.

Causes serious eye damage. Irritation of the eye tissue. Inflammation/damage of the eye tissue.

Symptoms/injuries after eye contact

Redness of the eye tissue.

Symptoms/injuries after ingestion : Fatal if swallowed. Toxic if swallowed. Swallowing a small quantity of this material will result in

serious health hazard.

SECTION 12: Ecological information

Toxicity

Polyethylene Glycol 200-600 (25322-68-3)		
LC50 fish 1	> 1000 mg/l (96 h; Pisces)	
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)	
LC50 fish 2	> 5000 mg/l (24 h; Carassius auratus)	
Threshold limit other aquatic organisms 1	<= 100 mg/l (96 h; Plankton)	
Threshold limit other aquatic organisms 2	> 1000 mg/l	
Threshold limit algae 2	500 mg/l (720 h; Algae; No effect)	

Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)

04/11/2014 EN (English US) 5/9

Safety Data Sheet

Additional information

Ecology - waste materials

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monda	y, March 26, 2012 / Rules and Regulations
Methanol (67-56-1)	
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)
12.2. Persistence and degradability	
JOHNSEN'S WINDSHIELD WASH CONCEN	NTRATION 12 FL.OZ.
Persistence and degradability	Not established.
Polyethylene Glycol 200-600 (25322-68-3)	
Persistence and degradability	Biodegradability in water: no data available.
Nonyl Nonoxynol-5 (9014-93-1)	
Persistence and degradability	Not established.
Hydrogen [4-[4-(Diethylamino)-2',4'-Disulp 17-9)	honatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129-
Persistence and degradability	Biodegradability in water: no data available.
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 % ThOD
12.3. Bioaccumulative potential	
JOHNSEN'S WINDSHIELD WASH CONCEN	NTRATION 12 FL.OZ.
Bioaccumulative potential	Not established.
Polyethylene Glycol 200-600 (25322-68-3)	
Log Pow	-1.2
Bioaccumulative potential	Bioaccumulation: not applicable.
Nonyl Nonoxynol-5 (9014-93-1)	
Bioaccumulative potential	Not established.
Hydrogen [4-[4-(Diethylamino)-2',4'-Disulp 17-9)	honatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129-
Log Pow	-5.340 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
Methanol (67-56-1)	
BCF fish 1	< 10 (Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
12.4. Mobility in soil	
Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
2.5. Other adverse effects	
Other information	: Avoid release to the environment.
SECTION 13: Disposal consideration	ons
13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional information	Handle empty containers with care because recidual vapors are flammable.

04/11/2014 EN (English US) 6/9

: Handle empty containers with care because residual vapors are flammable.

: Avoid release to the environment. Hazardous waste due to toxicity.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1230, Methanol Solution, 3, II, Limited Quantity ICAO/IATA (air): UN1230, Methanol Solution, 3 (6.1), II, Limited Quantity IMO/IMDG (water): UN1230, Methanol Solution, 3 (6.1), II, Limited Quantity

Special Provisions: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional

Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55

C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities

(in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

UN proper shipping name

Proper Shipping Name (DOT) : Methanol Solution

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** passenger vessel carrying a number of passengers limited to not more than the larger of 25

passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Subsidiary risks (IMDG)

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Subsidiary risks (IATA)

04/11/2014 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

JOHNSEN'S WINDSHIELD WASH CONCENTRATION 12 FL.OZ.	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

Methanol (67-56-1)	
Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

15.2. International regulations

CANADA

JOHNSEN'S WINDSHIELD WASH CONCENTRATION 12 FL.OZ.		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Methanol (67-56-1)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11

T; R23/24/25

T; R39/23/24/25

Full text of R-phrases: see section 16

15.2.2. National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Indication of changes : Revision - See : *.


Other information : None.

Full text of H-phrases: see section 16:

and the principles of the control of	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

NFPA health hazard

 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.



04/11/2014 EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

04/11/2014 EN (English US) 9/9