



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

**SECTION 1. IDENTIFICATION**

Product name : Valvoline™ MARINE OUTBOARD 2-STROKE TC-W3  
Motor Oil

Product code : 773735

**Manufacturer or supplier's details**

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone  
number : +1-800-VALVOLINE (+1-800-825-8654)

---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 4

Skin irritation : Category 2

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

H315 Causes skin irritation.

Precautionary statements

:

**Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 If skin irritation occurs: Get medical advice/  
attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or  
alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste  
disposal plant.

**Other hazards**

Static-accumulating flammable liquid.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture

:

Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 30 - < 40
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	>= 30 - < 40
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	>= 20 - < 30
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4	>= 20 - < 30
Naphtha (petroleum), heavy aromatic	64742-94-5	>= 1.5 - < 5

Actual concentration is withheld as a trade secret

---

**SECTION 4. FIRST AID MEASURES**



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Causes skin irritation. No symptoms known or expected.
Notes to physician	: Treat symptomatically.  No hazards which require special first aid measures.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: carbon dioxide and carbon monoxide
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.  
Keep in a well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.



**SAFETY DATA SHEET**  
 Valvoline™ MARINE OUTBOARD 2-STROKE  
 TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates, petroleum, solvent- refined heavy paraffinic	64741-88-4	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
RESIDUAL OILS (PETROLEUM), SOLVENT- REFINED	64742-01-4	ST ESL	1,000 µg/m3	TX ESL
		AN ESL	100 µg/m3	TX ESL

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : < -38 °F / < -39 °C

Boiling point/boiling range : > 356 °F / 180 °C  
(1013 hPa)

Flash point : 196 °F / 91 °C

Evaporation rate : 0.1  
butyl acetate=1

Flammability (solid, gas) : No data available

Flammability (liquids) : Static-accumulating flammable liquid.

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 6.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapour pressure : 0.2 mmHg (68 °F / 20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 0.866 g/cm<sup>3</sup> (68 °F / 20 °C)



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	36.8 mm <sup>2</sup> /s (104 °F / 40 °C)
Oxidizing properties	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5 g/kg

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
---------------------	---	---------------------------



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: The toxicological data has been taken from products of similar composition.

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**Naphtha (petroleum), heavy aromatic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m3





**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : May cause skin irritation in susceptible persons.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Species : Rabbit  
Result : No skin irritation

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Assessment : Irritating to skin.  
Result : Irritating to skin.

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Species : Rabbit  
Result : No skin irritation

**Naphtha (petroleum), heavy aromatic:**

Result : Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Species : Rabbit  
Result : No eye irritation

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Species : Rabbit  
Result : Slight, transient irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Genotoxicity in vitro : Test Type: Ames test  
Result: negative

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

No aspiration toxicity classification

**Naphtha (petroleum), heavy aromatic:**

May be fatal if swallowed and enters airways.



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated  $\geq$  1,000 mg/l  
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Scud (Gammarus pulex)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: semi-static test  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)):  $\geq$  100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

**Naphtha (petroleum), heavy aromatic:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Persistence and degradability**

**Components:**

**Distillates, petroleum, solvent-refined heavy paraffinic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:**

Biodegradability : Result: Inherently biodegradable.  
Biodegradation: 58.6 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
Remarks: The toxicological data has been taken from products of similar composition.

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.



**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Hazard not otherwise classified (physical hazards)  
Skin corrosion or irritation

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM/ Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations**

**Massachusetts Right To Know**

Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8

**Pennsylvania Right To Know**

LUBRICANT ADDITIVE	Not Assigned
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7





**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8
RESIDUAL OILS (PETROLEUM), SOLVENT-REFINED	64742-01-4

**Maine Chemicals of High Concern**

Product does not contain any listed chemicals

**Vermont Chemicals of High Concern**

Product does not contain any listed chemicals

**Washington Chemicals of High Concern**

Product does not contain any listed chemicals

**California Prop. 65**

WARNING: This product can expose you to chemicals including DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC, DISTILLATES (PETROLEUM), HYDROTREATED LIGHT, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California List of Hazardous Substances**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4

**California Permissible Exposure Limits for Chemical Contaminants**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8

**The components of this product are reported in the following inventories:**

TCSI	: Not in compliance with the inventory
TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AIIC	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

TECI : Not in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	/	2
<b>FLAMMABILITY</b>		2
<b>PHYSICAL HAZARD</b>		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants



**Valvoline™**  
**Global**

**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

TX ESL	:	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality)
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
TX ESL / ST ESL	:	Short-Term ESL:
TX ESL / AN ESL	:	Annual ESL:

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/15/2023



**Valvoline™**

**Global**

**SAFETY DATA SHEET**  
Valvoline™ MARINE OUTBOARD 2-STROKE  
TC-W3 Motor Oil

Version: 3.0

Revision Date: 06/15/2023

Print Date:  
06/21/2023

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0172415