Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 03/31/2016 Supersedes:05/18/2015

1.1. Product identifier	the substance/mixture and of the company/undertaking
Product form	: Mixture
Trade name	: PRONTO NON-CHLORINATED BRAKE CLEANER 14 OZ.
Product code	: 817202
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Use of the substance/mixture	: Brake Parts Cleaner
1.3. Details of the supplier of the supplication of the suppli	ne safety data sheet
National Pronto Association 2601 Heritage Ave Grapevine, TX 76051 T 817-430-9449	
1.4. Emergency telephone nun	iber
Emergency number	: CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1.

GHS-US classification

Flam. Aerosol 2	H223
Compressed gas	H280
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Repr. 2	H361
STOT SE 1	H370
STOT SE 3	H336
STOT RE 2	H373

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)

				\sim		\sim	
		GHS02	GHS04	GHS06	GHS07	GHS08	
Signal word (GHS-US)	:	Danger					
Hazard statements (GHS-US)	 H223 - Flammable aerosol H280 - Contains gas under pressure; may explode if heated H300 - Fatal if swallowed H315 - Causes skin irritation H318 - Causes serious eye damage H336 - May cause drowsiness or dizziness H360 - May damage fertility or the unborn child H370 - Causes damage to organs H373 - May cause damage to organs through prolonged or repeated exposure 						
Precautionary statements (GHS-US)	:	P210 - Keep av P211 - Do not s P251 - Pressuri P260 - Do not b P261 - Avoid br P264 - Wash af P270 - Do not e P271 - Use only P280 - Wear pr P301+P310 - If P302+P352 - If	andle until all sa vay from heat,sp pray on an oper zed container: D oreathe dust,fum fected areas tho at, drink or smol y outdoors or in a otective gloves,p swallowed: Imm on skin: Wash w	afety precautions arks,open flame of flame or other i bo not pierce or b es,gas,mist,vapo roughly after han ke when using the a well-ventilated protective clothin rediately call a po vith plenty of soa	s,hot surfaces gnition source burn, even after u or spray r spray hdling his product area g,eye protection. bison control cen p and water	JSE	
31/03/2016		EN (English US)					1/12

Version: 1.1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a poison center/doctor P308+P313 - If exposed or concerned: Get medical advice/attention P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell. P314 - Get medical advice/attention if you feel unwell P321 - Specific treatment: See section 4.1 on SDS P330 - Rinse mouth P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P400 - P403 - Protect from sunlight. Store in a well-ventilated place
P405 - Store locked up

2.3. Other hazards

Other hazards not contributing to the

: Contains gas under pressure; may explode if heated. None under normal conditions.

classification

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Toluene	(CAS No) 108-88-3	30 - 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Methanol	(CAS No) 67-56-1	30 - 50	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Acetone	(CAS No) 67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	5 - 10	Compressed gas, H280

The exact percentage is a trade secret.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	 Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation	: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Cal a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	Immediately call a poison center or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persist. Direct contact with the eyes is likely to be irritating.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call poison center or doctor/physician.
4.2. Most important symptoms and eff	ects, both acute and delayed
Symptoms/injuries	: Irritation of the respiratory tract. If you feel unwell, seek medical advice. Suspected of damagin fertility or the unborn child. Causes damage to organs.
Symptoms/injuries after inhalation	: Coughing. Irritation of the respiratory tract. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

ccording to Federal Register / Vol. 77, No. 58 / Mo	nday, March 26, 2012 / Rules and Regulations		
Symptoms/injuries after eye contact	: May cause severe irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.		
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.		
4.3. Indication of any immediate me	dical attention and special treatment needed		
No additional information available			
SECTION 5: Firefighting measure	9S		
5.1. Extinguishing media			
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.		
Unsuitable extinguishing media	: Do not use a heavy water stream.		
5.2. Special hazards arising from the	e substance or mixture		
Fire hazard	: Flammable aerosol.		
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.		
5.3. Advice for firefighters			
Firefighting instructions	 Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fir reaches explosives. Evacuate area. 		
Protection during firefighting Other information	 Do not enter fire area without proper protective equipment, including respiratory protection. Aerosol Level 2. 		
SECTION 6: Accidental release n			
	e equipment and emergency procedures		
General measures	: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.		
6.1.1. For non-emergency personnel			
Protective equipment	: Gloves. Safety glasses.		
Emergency procedures	: Evacuate unnecessary personnel.		
6.1.2. For emergency responders			
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.		
Emergency procedures	: Ventilate area.		
6.2. Environmental precautions			
Prevent entry to sewers and public waters. I	Notify authorities if liquid enters sewers or public waters.		
6.3. Methods and material for contain			
For containment	: Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump int suitable containers.		
Methods for cleaning up	: Store away from other materials.		
6.4. Reference to other sections			
See Heading 8. Exposure controls and pers			
SECTION 7: Handling and storag	e		
7.1. Precautions for safe handling	. Hereaders words due to establish the of each size. Descendend exclusions Descent sizes on		
Additional hazards when processed	 Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use. Weah banda and after expressed grass with mild soon and water before exting driphing or 		
Precautions for safe handling	 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breather dust,fumes,gas,mist,vapor spray. 		
Hygiene measures	: Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.		
7.2. Conditions for safe storage, inc			
Technical measures	 Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. 		
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.		
Incompatible products	: Strong bases. Strong acids.		
31/03/2016	EN (English US) 3/12		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials

Storage area

: Sources of ignition. Direct sunlight. Heat sources.: Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

ACGIH TWA (ppm) ACGIH STEL (ppm) ACGIH Ceiling (ppm) OSHA PEL (TWA) (ppm) OSHA PEL (Ceiling) (ppm) ACGIH TWA (mg/m³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	1 ppm 5 ppm 25 ppm 1 ppm 5 ppm 75 mg/m ³ 20 ppm
ACGIH STEL (ppm) ACGIH Ceiling (ppm) OSHA PEL (TWA) (ppm) OSHA PEL (Ceiling) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	5 ppm 25 ppm 1 ppm 5 ppm 75 mg/m ³
ACGIH STEL (ppm) ACGIH Ceiling (ppm) OSHA PEL (TWA) (ppm) OSHA PEL (Ceiling) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	5 ppm 25 ppm 1 ppm 5 ppm 75 mg/m ³
ACGIH Ceiling (ppm) OSHA PEL (TWA) (ppm) OSHA PEL (Ceiling) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	25 ppm 1 ppm 5 ppm 75 mg/m ³
OSHA PEL (TWA) (ppm) OSHA PEL (Ceiling) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	1 ppm 5 ppm 75 mg/m ³
OSHA PEL (Ceiling) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	5 ppm 75 mg/m ³
ACGIH TWA (mg/m ³) ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	75 mg/m ³
ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	•
ACGIH TWA (ppm) OSHA PEL (TWA) (ppm)	<u> </u>
OSHA PEL (TWA) (ppm)	20 ppm
() (I)	zo ppm
OSHA PEL (Ceiling) (ppm)	200 ppm
	300 ppm
nder Pressure (124-38-9)	
ACGIH TWA (mg/m ³)	9000 mg/m³
ACGIH TWA (ppm)	5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH STEL (mg/m³)	54000
ACGIH STEL (ppm)	30000 ppm
OSHA PEL (TWA) (mg/m³)	9000 mg/m³
OSHA PEL (TWA) (ppm)	5000 ppm
	-
ACGIH TWA (mg/m³)	1188 mg/m ³
ACGIH TWA (ppm)	500 ppm
ACGIH STEL (mg/m³)	1782 mg/m ³
ACGIH STEL (ppm)	750 ppm
OSHA PEL (TWA) (mg/m³)	2400 mg/m ³
OSHA PEL (TWA) (ppm)	1000 ppm
	-
ACGIH TWA (mg/m³)	262 mg/m ³
ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH STEL (mg/m³)	328 mg/m ³
ACGIH STEL (ppm)	250 ppm
	260 mg/m ³
OSHA PEL (TWA) (mg/m³)	200 mg/m ⁻
	OSHA PEL (TWA) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (ppm) ACGIH STEL (mg/m ³) ACGIH STEL (ppm) OSHA PEL (TWA) (mg/m ³) OSHA PEL (TWA) (ppm) ACGIH TWA (mg/m ³) ACGIH TWA (mg/m ³) ACGIH STEL (ppm)

8.2. Exposure controls Appropriate engineering controls

Personal protective equipment

Materials for protective clothing

Skin and body protection

: Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

: Gloves. Safety glasses. Avoid all unnecessary exposure.



: GIVE EXCELLENT RESISTANCE:

: Wear protective gloves.

: Chemical goggles or safety glasses.

: Wear suitable protective clothing.

Hand protection

Eye protection

PRONTO NON-CHLORINATED BRAKE CLEANER 14 OZ. Safety Data Sheet

Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Consumer exposure controls	: Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke during use.
SECTION 9: Physical and chemica	I properties
9.1. Information on basic physical and	I chemical properties
Physical state	: Gas
Appearance	: Liquid.
Color	: Colourless to light yellow.
Odor	: Solvent-like odour. Strong.
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: <-78.9 °C (Lowest Component-Acetone)
Freezing point	: No data available
Boiling point	: 56 °C (Lowest Component-Acetone)
Flash point	: -18 °C (Lowest Component-Acetone)
Auto-ignition temperature	: 385 °C (Lowest Component-Acetone)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.82
Solubility	: Moderately soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Heating may cause a fire or explosion.
Oxidizing properties	: No data available
Explosion limits	: No data available
9.2. Other information	
VOC content	: 70 %
Gas group	: Compressed gas

SECTIO	DN 10: Stability and reactivity
10.1.	Reactivity
No additio	onal information available
10.2.	Chemical stability
Flammab ignition.	le aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of
10.3.	Possibility of hazardous reactions
Not estab	lished.
10.4.	Conditions to avoid
Direct sur	nlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.
10.5.	Incompatible materials
Strong ac	ids. Strong bases.
10.6.	Hazardous decomposition products
	ne Carbon monoxide. Carbon dioxide.
SECTIO	DN 11: Toxicological information
11.1.	Information on toxicological effects

Acute toxicity

: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg
	bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Benzene (71-43-2)	
IARC group	1
Toluene (108-88-3)] ·
IARC group	3
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Causes damage to organs. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/injuries after inhalation	: Coughing. Irritation of the respiratory tract. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: May cause severe irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Benzene (71-43-2)		
LC50 fish 1	5.3 mg/l (LC50; 96 h; Salmo gairdneri)	
EC50 Daphnia 2	10 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)	
Threshold limit algae 1	100 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)	
Carbon Dioxide, Liquefied, Under	Pressure (124-38-9)	
LC50 fish 1	35 mg/l (LC50; 96 h; Salmo gairdneri)	
Acetone (67-64-1)		
EC50 Daphnia 2	12600 mg/l (LC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)	
Acetone (67-64-1)		
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)	
31/03/2016	EN (English US)	6/12

3	,,
Acetone (67-64-1)	
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)
Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system;
	Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)
2.2. Persistence and degradability	
PRONTO NON-CHLORINATED BRAKE CLI	EANER 14 OZ.
Persistence and degradability	Not established.
Benzene (71-43-2)	
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water.
	Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	2.18 g O ₂ /g substance
Chemical oxygen demand (COD)	2.15 g O ₂ /g substance
ThOD	3.10 g O ₂ /g substance
BOD (% of ThOD)	0.70
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69
Carbon Dioxide, Liquefied, Under Pressure	e (124-38-9)
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Acetone (67-64-1)	
Persistence and degradability	Not established.
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under
	anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.20 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 (Literature study)
2.3. Bioaccumulative potential	
PRONTO NON-CHLORINATED BRAKE CLI	EANER 14 OZ.
Bioaccumulative potential	Not established.
Bioaccumulative potential	
Benzene (71-43-2)	
•	19 (BCF)
Benzene (71-43-2)	19 (BCF) < 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus; Flow-through system; Fresh water; Experimental value)
Benzene (71-43-2) BCF fish 1	< 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus;

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	/ / , i to / initial with a set of the set	larch 26, 2012 / Rules and Regulations
Benzene (71-43-2)		
Log Pow		2.13 (Experimental value)
Bioaccumulative potentia	al	Low potential for bioaccumulation (BCF < 500).
Toluene (108-88-3)		
BCF fish 2		90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Log Pow		2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potentia	al	Low potential for bioaccumulation (BCF < 500).
Carbon Dioxide, Lique	ied, Under Pressure (1	24-38-9)
Log Pow		0.83 (Experimental value)
Bioaccumulative potentia	al	Bioaccumulation: not applicable.
Acetone (67-64-1)		
Bioaccumulative potentia	al	Not established.
Acetone (67-64-1)		
BCF fish 1		0.69 (Pisces)
BCF other aquatic organ	isms 1	3
Log Pow		-0.24 (Test data)
Bioaccumulative potentia	al	Not bioaccumulative. Not established.
Methanol (67-56-1)		
BCF fish 1		< 10 (BCF; 72 h; Leuciscus idus)
Log Pow		-0.77 (Experimental value; Other)
Bioaccumulative potentia	al	Low potential for bioaccumulation (BCF < 500).
2.4. Mobility in soil		
Benzene (71-43-2)		
Surface tension		0.029 N/m (20 °C)
Log Koc		Koc.134.1; QSAR
Toluene (108-88-3)		
Surface tension		0.03 N/m (20 °C)
		0.00 Nill (20 0)
Acetone (67-64-1) Surface tension		0.0237 N/m (20 °C)
		0.0237 14/11 (20 C)
Methanol (67-56-1)		
Surface tension		0.023 N/m (20 °C)
Log Koc		Koc,PCKOCWIN v1.66; 1; Calculated value
2.5. Other adverse	effects	
Other information	:	: Avoid release to the environment.
SECTION 13: Dispo		
3.1. Waste treatmen		
Vaste disposal recommer	idations :	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
dditional information	:	Flammable vapors may accumulate in the container.
cology - waste materials	:	Avoid release to the environment. Hazardous waste due to toxicity.
SECTION 14: Trans		Ν
IS DOT (ground):	IN1950 Apropole 21 1	imited Quantity
·• /	UN1950, Aerosols, 2.1, Limited Quantity	
. ,	UN1950, Aerosols, 2.1, Limited Quantity	
MO/IMDG (water):	UN1950, Aerosols, 2.1 ,	Limited Quantity
pecial Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols		
4.2. UN proper ship	ning name	
		: Aerosols
Proper Shipping Name (D		
		Flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

according to Federal Register / Vol. 77, No. 58 / Monday, N	Aarch 26, 2012 / Rules and Regulations
Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Packaging Exceptions (49 CFR 173.xxx)	 N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols 306
DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	: None : None
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport	
No additional information available	
Transport by sea	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
DOT Vessel Stowage Other	: 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Air transport	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
SECTION 15: Regulatory information	
15.1. US Federal regulations	
PRONTO NON-CHLORINATED BRAKE CLEA	NER 14 OZ.
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard
Benzene (71-43-2)	
Listed on the United States TSCA (Toxic Substa Subject to reporting requirements of United State	
Toluene (108-88-3)	
Subject to reporting requirements of United State Listed on the United States TSCA (Toxic Substa Listed on the United States SARA Section 302	es SARA Section 313 Inces Control Act) inventory
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
Carbon Dioxide, Liquefied, Under Pressure (1	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard
Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substa Subject to reporting requirements of United State	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
	Delayed (chronic) health hazard
Methanol (67-56-1) Subject to reporting requirements of United State	as SARA Section 313
Listed on the United States TSCA (Toxic Substa Listed on the United States SARA Section 302 Listed on the United States SARA Section 355	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

CANADA		
PRONTO NON-CHLORINATED BRAKE CLEANER 14 OZ.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol	
Benzene (71-43-2)		
Listed on the Canadian DSL (Domestic Substances List)		
Toluene (108-88-3)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Acetone (67-64-1)		
Listed on the Canadian DSL (Domestic Substanc	es List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Methanol (67-56-1)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

Toluene (108-88-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Acetone (67-64-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Methanol (67-56-1)	

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63 F; R11 T; R23/24/25 T; R39/23/24/25 Xn; R48/20 Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

Benzene (71-43-2)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the supariese Lines (Lxisting & New Chemical Substances) inventory
Toluene (108-88-3)
Acetone (67-64-1)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

3	, , , , , , , , , , , , , , , , , , , ,	, 5		
15.3. US State regulation				
PRONTO NON-CHLORIN U.S California - Proposit	ATED BRAKE CLEANER 14	-		
-	0	No		
U.S California - Proposit Toxicity	·			
U.S California - Proposit Toxicity - Female	ion 65 - Reproductive	No		
U.S California - Proposit Toxicity - Male	ion 65 - Reproductive	No		
State or local regulations		U.S California - Proposition	65 - Maximum Allowable Dose	Levels (MADL)
Benzene (71-43-2)				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
Yes	Yes	No	Yes	
Toluene (108-88-3)				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
No	Yes	No	No	
Carbon Dioxide, Liquefie	ed, Under Pressure (124-38-9	3)		
U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	Non-significant risk level (NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	
No	No	No	No	
Acetone (67-64-1)				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
No	No	No	No	
Acetone (67-64-1)	•	·	·	
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
Yes	No	No	No	
Methanol (67-56-1)	•	•		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	
Benzene (71-43-2)				
State or local regulations	8			
	ion 65 - Maximum Allowable [(Right to Know) List	Dose Levels (MADL)		
Toluono (409.90.0)				
Toluene (108-88-3) State or local regulations	8			
U.S California - Proposit U.S New Jersey - Specia New Jersey Right-to-Know U.S Massachusetts - Rig Rhode Island Right to Kno U.S Michigan - Critical M	ion 65 - Maximum Allowable I al Health Hazards Substances / ht To Know List w faterials List onmental Hazardous Substanc	List		
31/03/2016		inglish US)		11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)

Toluene (108-88-3)	
U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
Acetone (67-64-1)	
State or local regulations	
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL) Benzene 71-43-2 U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List	
Methanol (67-56-1)	
State or local regulations	
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL) New Jersey Right-to-Know Florida Right to Know U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List	

SECTION 16: Other information

: Revision - See : *.

Indication of changes Other information

: NFPA Aerosol Level 3. None.

Full text of H-phrases:

text of h-phrases.		
H223	Flammable aerosol	
H225	Highly flammable liquid and vapor	
H280	Contains gas under pressure; may explode if heated	
H301	Toxic if swallowed	
H304	May be fatal if swallowed and enters airways	
H311	Toxic in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H331	Toxic if inhaled	
H336	May cause drowsiness or dizziness	
H361	Suspected of damaging fertility or the unborn child	
H370	Causes damage to organs	
H373	May cause damage to organs through prolonged or repeated	
	exposure	

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 1 Slight Hazard
Personal Protection	: B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.