

# 97956



## Safety Data Sheet

Copyright, 2017, 3M Company.  
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 29-3109-5 | <b>Version Number:</b>  | 4.00     |
| <b>Issue Date:</b>     | 04/25/17  | <b>Supercedes Date:</b> | 03/03/15 |

### SECTION 1: Identification

**1.1. Product identifier**  
Super 77 Aerosol Spray Low 25% VOC

**Product Identification Numbers**  
62-4876-4930-3, 62-4876-4935-2

**1.2. Recommended use and restrictions on use**

**Recommended use**  
Adhesive, Industrial use

**1.3. Supplier's details**  
**MANUFACTURER:** 3M  
**DIVISION:** Industrial Adhesives and Tapes Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

**1.4. Emergency telephone number**  
1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

**2.1. Hazard classification**  
Flammable Aerosol: Category 1.  
Gas Under Pressure: Dissolved gas.  
Serious Eye Damage/Irritation: Category 2A.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.

**2.2. Label elements**  
**Signal word**  
Danger

**Symbols**  
Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Causes damage to organs:  
cardiovascular system |

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see Notes to Physician on this label).

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**2.3. Hazards not otherwise classified****Supplemental Information:**

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**SECTION 3: Composition/information on ingredients**

| Ingredient               | C.A.S. No.    | % by Wt                |
|--------------------------|---------------|------------------------|
| Acetone                  | 67-64-1       | 35 - 45 Trade Secret * |
| Non-hazardous components | Trade Secret* | 10 - 25 Trade Secret * |
| 1,1-Difluoroethane       | 75-37-6       | 10 - 15 Trade Secret * |
| Cyclohexane              | 110-82-7      | 5 - 15 Trade Secret *  |
| Propane                  | 74-98-6       | 10 - 15 Trade Secret * |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

Substance

Carbon monoxide  
Carbon dioxide

Condition

During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.



**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient  | C.A.S. No. | Agency | Limit type                   | Additional Comments            |
|-------------|------------|--------|------------------------------|--------------------------------|
| Cyclohexane | 110-82-7   | ACGIH  | TWA:100 ppm                  |                                |
| Cyclohexane | 110-82-7   | OSHA   | TWA:1050 mg/m3(300 ppm)      |                                |
| Acetone     | 67-64-1    | OSHA   | TWA:2400 mg/m3(1000 ppm)     |                                |
| Acetone     | 67-64-1    | ACGIH  | TWA:250 ppm;STEL:500 ppm     | A4: Not class. as human carcin |
| Propane     | 74-98-6    | ACGIH  | Limit value not established: |                                |
| Propane     | 74-98-6    | OSHA   | TWA:1800 mg/m3(1000 ppm)     |                                |

|                    |         |      |                          |
|--------------------|---------|------|--------------------------|
| 1,1-Difluoroethane | 75-37-6 | AIHA | TWA:2700 mg/m3(1000 ppm) |
|--------------------|---------|------|--------------------------|

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Nitrile Rubber

Polyvinyl Alcohol (PVA)

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                           |   |
|---------------------------|---|
| General Physical Form:    | Liquid                                    |
| Specific Physical Form:   | Aerosol                                   |
| Odor, Color, Grade:       | clear, solvent odor                       |
| Odor threshold            | <i>No Data Available</i>                  |
| pH                        | <i>Not Applicable</i>                     |
| Melting point             | <i>Not Applicable</i>                     |
| Boiling Point             | -44 °F [ <i>Details:Acetone</i> ]         |
| Flash Point               | -156 °F [ <i>Test Method:Closed Cup</i> ] |
| Evaporation rate          | > 1 [ <i>Ref Std:BUOAC=1</i> ]            |
| Flammability (solid, gas) | Not Applicable                            |
| Flammable Limits(LEL)     | 1.3 % volume                              |



|   |  |
|---|--|
| Flammable Limits(UEL)                   | 12.8 % volume                                    |
| Vapor Pressure                          | <=4137 mmHg [@ 68 °F]                            |
| Vapor Density                           | > 1 [Ref Std: AIR=1]                             |
| Density                                 | 0.80 g/ml  |
| Specific Gravity                        | 0.80 [Ref Std: WATER=1]                          |
| Solubility in Water                     | Nil  |
| Solubility- non-water                   | No Data Available                                |
| Partition coefficient: n-octanol/ water | No Data Available                                |
| Autoignition temperature                | No Data Available                                |
| Decomposition temperature               | No Data Available                                |
| Viscosity                               | <=100 centipoise [@ 73.4 °F ]                    |
| Molecular weight                        | No Data Available                                |
| Percent volatile                        | <=80.6 % weight                                  |
| VOC Less H2O & Exempt Solvents          | <=25 % [Test Method:calculated per CARB title 2] |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

### 10.5. Incompatible materials

Not determined

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Prolonged or repeated exposure may cause:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name               | Route                      | Species | Value  |
|--------------------|----------------------------|---------|--|
| Overall product    | Dermal                     |         | No data available; calculated ATE >5,000 mg/kg |
| Overall product    | Inhalation-Vapor(4 hr)     |         | No data available; calculated ATE >50 mg/l     |
| Overall product    | Ingestion                  |         | No data available; calculated ATE >5,000 mg/kg |
| Acetone            | Dermal                     | Rabbit  | LD50 > 15,688 mg/kg                            |
| Acetone            | Inhalation-Vapor (4 hours) | Rat     | LC50 76 mg/l                                   |
| Acetone            | Ingestion                  | Rat     | LD50 5,800 mg/kg                               |
| Propane            | Inhalation-Gas (4 hours)   | Rat     | LC50 > 200,000 ppm                             |
| 1,1-Difluoroethane | Inhalation-Gas (4 hours)   | Rat     | LC50 > 437,000 ppm                             |
| 1,1-Difluoroethane | Ingestion                  | Rat     | LD50 > 1,500 mg/kg                             |
| Cyclohexane        | Dermal                     | Rat     | LD50 > 2,000 mg/kg                             |
| Cyclohexane        | Inhalation-Vapor (4 hours) | Rat     | LC50 > 32.9 mg/l                               |



|             |           |     |                  |
|-------------|-----------|-----|------------------|
| Cyclohexane | Ingestion | Rat | LD50 6,200 mg/kg |
|-------------|-----------|-----|------------------|

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name        | Species | Value              |
|-------------|---------|--------------------|
| Acetone     | Mouse   | Minimal irritation |
| Propane     | Rabbit  | Minimal irritation |
| Cyclohexane | Rabbit  | Mild irritant      |

**Serious Eye Damage/Irritation**

| Name        | Species | Value           |
|-------------|---------|-----------------|
| Acetone     | Rabbit  | Severe irritant |
| Propane     | Rabbit  | Mild irritant   |
| Cyclohexane | Rabbit  | Mild irritant   |

**Skin Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name               | Route    | Value  |
|--------------------|----------|--|
| Acetone            | In vivo  | Not mutagenic  |
| Acetone            | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Propane            | In Vitro | Not mutagenic  |
| 1,1-Difluoroethane | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 1,1-Difluoroethane | In vivo  | Some positive data exist, but the data are not sufficient for classification |
| Cyclohexane        | In Vitro | Not mutagenic  |
| Cyclohexane        | In vivo  | Some positive data exist, but the data are not sufficient for classification |

**Carcinogenicity**

| Name               | Route         | Species                 | Value  |
|--------------------|---------------|-------------------------|--|
| Acetone            | Not Specified | Multiple animal species | Not carcinogenic   |
| 1,1-Difluoroethane | Inhalation    | Rat                     | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name               | Route      | Value  | Species | Test Result           | Exposure Duration    |
|--------------------|------------|--|---------|-----------------------|----------------------|
| Acetone            | Ingestion  | Some positive male reproductive data exist, but the data are not sufficient for classification | Rat     | NOAEL 1,700 mg/kg/day | 13 weeks             |
| Acetone            | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification     | Rat     | NOAEL 5.2 mg/l        | during organogenesis |
| 1,1-Difluoroethane | Inhalation | Not toxic to development   | Rat     | NOAEL 50,000 ppm      | during organogenesis |
| Cyclohexane        | Inhalation | Not toxic to female reproduction   | Rat     | NOAEL 24              | 2 generation         |



|             |            |  |     |                       |              |
|-------------|------------|--|-----|-----------------------|--------------|
| Cyclohexane | Inhalation | Not toxic to male reproduction   | Rat | mg/l<br>NOAEL 24 mg/l | 2 generation |
| Cyclohexane | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 6.9 mg/l        | 2 generation |

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

| Name               | Route      | Target Organ(s)                   | Value  | Species                | Test Result         | Exposure Duration      |
|--------------------|------------|-----------------------------------|--|------------------------|---------------------|------------------------|
| Acetone            | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human                  | NOAEL Not available |                        |
| Acetone            | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human                  | NOAEL Not available |                        |
| Acetone            | Inhalation | immune system                     | Some positive data exist, but the data are not sufficient for classification | Human                  | NOAEL 1.19 mg/l     | 6 hours                |
| Acetone            | Inhalation | liver                             | Some positive data exist, but the data are not sufficient for classification | Guinea pig             | NOAEL Not available |                        |
| Acetone            | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Human                  | NOAEL Not available | poisoning and/or abuse |
| Propane            | Inhalation | cardiac sensitization             | Causes damage to organs  | Human                  | NOAEL Not available |                        |
| Propane            | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human                  | NOAEL Not available |                        |
| Propane            | Inhalation | respiratory irritation            | All data are negative  | Human                  | NOAEL Not available |                        |
| 1,1-Difluoroethane | Inhalation | cardiac sensitization             | Causes damage to organs  | Human and animal       | NOAEL Not available | poisoning and/or abuse |
| 1,1-Difluoroethane | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human and animal       | NOAEL 100,000 ppm   |                        |
| 1,1-Difluoroethane | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Not available          | NOAEL Not available | not available          |
| Cyclohexane        | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human and animal       | NOAEL Not available |                        |
| Cyclohexane        | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human and animal       | NOAEL Not available |                        |
| Cyclohexane        | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Professional judgement | NOAEL Not available |                        |

**Specific Target Organ Toxicity - repeated exposure**

| Name    | Route      | Target Organ(s)       | Value  | Species    | Test Result         | Exposure Duration |
|---------|------------|-----------------------|--|------------|---------------------|-------------------|
| Acetone | Dermal     | eyes                  | Some positive data exist, but the data are not sufficient for classification | Guinea pig | NOAEL Not available | 3 weeks           |
| Acetone | Inhalation | hematopoietic system  | Some positive data exist, but the data are not sufficient for classification | Human      | NOAEL 3 mg/l        | 6 weeks           |
| Acetone | Inhalation | immune system         | Some positive data exist, but the data are not sufficient for classification | Human      | NOAEL 1.19 mg/l     | 6 days            |
| Acetone | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Guinea pig | NOAEL 119 mg/l      | not available     |

|                    |            |   |  |        |                        |          |
|--------------------|------------|---|--|--------|------------------------|----------|
| Acetone            | Inhalation | heart   liver   | All data are negative  | Rat    | NOAEL 45 mg/l          | 8 weeks  |
| Acetone            | Ingestion  | kidney and/or bladder   | Some positive data exist, but the data are not sufficient for classification | Rat    | NOAEL 900 mg/kg/day    | 13 weeks |
| Acetone            | Ingestion  | heart   | Some positive data exist, but the data are not sufficient for classification | Rat    | NOAEL 2,500 mg/kg/day  | 13 weeks |
| Acetone            | Ingestion  | hematopoietic system  | Some positive data exist, but the data are not sufficient for classification | Rat    | NOAEL 200 mg/kg/day    | 13 weeks |
| Acetone            | Ingestion  | liver   | Some positive data exist, but the data are not sufficient for classification | Mouse  | NOAEL 3,896 mg/kg/day  | 14 days  |
| Acetone            | Ingestion  | eyes  | All data are negative  | Rat    | NOAEL 3,400 mg/kg/day  | 13 weeks |
| Acetone            | Ingestion  | respiratory system  | All data are negative  | Rat    | NOAEL 2,500 mg/kg/day  | 13 weeks |
| Acetone            | Ingestion  | muscles   | All data are negative  | Rat    | NOAEL 2,500 mg/kg      | 13 weeks |
| Acetone            | Ingestion  | skin   bone, teeth, nails, and/or hair                            | All data are negative  | Mouse  | NOAEL 11,298 mg/kg/day | 13 weeks |
| 1,1-Difluoroethane | Inhalation | hematopoietic system   kidney and/or bladder   respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat    | NOAEL 25,000 ppm       | 2 years  |
| Cyclohexane        | Inhalation | liver   | Some positive data exist, but the data are not sufficient for classification | Rat    | NOAEL 24 mg/l          | 90 days  |
| Cyclohexane        | Inhalation | auditory system   | Some positive data exist, but the data are not sufficient for classification | Rat    | NOAEL 1.7 mg/l         | 90 days  |
| Cyclohexane        | Inhalation | kidney and/or bladder   | Some positive data exist, but the data are not sufficient for classification | Rabbit | NOAEL 2.7 mg/l         | 10 weeks |
| Cyclohexane        | Inhalation | hematopoietic system  | Some positive data exist, but the data are not sufficient for classification | Mouse  | NOAEL 24 mg/l          | 14 weeks |
| Cyclohexane        | Inhalation | peripheral nervous system   | All data are negative  | Rat    | NOAEL 8.6 mg/l         | 30 weeks |

**Aspiration Hazard**

| Name        | Value             |
|-------------|-------------------|
| Cyclohexane | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**



**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - Yes    Pressure Hazard - Yes    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - No

**EPCRA 311/312 Hazard Classifications (effective January 1, 2018):**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

**Health Hazards**

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u>      |
|-------------------|------------------|---------------------|
| Cyclohexane       | 110-82-7         | Trade Secret 5 - 15 |

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 4 Instability: 0 Special Hazards: None  
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 29-3109-5 | <b>Version Number:</b>  | 4.00     |
| <b>Issue Date:</b>     | 04/25/17  | <b>Supersedes Date:</b> | 03/03/15 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)





## Transport Information Document

Date: July 27, 2018

3M ID Number: 62-4876-4930-3

Product Description: 3M(TM) Super 77(TM) CA Multi-Purpose Spray Adhesive - Low VOC< 25% Clear, Net Wt 18.0 oz, 12 per case

Transport Protective Service: PROTECTIVE SERVICE NOT REQUIRED

NMFC Item: 004620 NMFC Sub: 06 NMFC Class: 060.0

Flash Point (Closed-cup): No Flash Point

UNITED STATES DEPARTMENT OF TRANSPORTATION - GROUND (U.S. DOT, 49 CFR)

LIMITED QUANTITY

UNITED STATES DEPARTMENT OF TRANSPORTATION - VESSEL (U.S. DOT, 49 CFR)

UN1950, AEROSOLS, 2.1, LIMITED QUANTITY

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA)

UN1950, AEROSOLS, FLAMMABLE, 2.1

INTERNATIONAL MARITIME ORGANIZATION (IMO)

UN1950, AEROSOLS, 2.1, LIMITED QUANTITY

The classification is authorized by the Competent Authority of the United States of America and may not meet the requirements of other competent authorities.

These transportation classifications are provided as a customer service. AS THE SHIPPER YOU REMAIN RESPONSIBLE FOR COMPLYING WITH ALL THE APPLICABLE LAWS AND REGULATIONS, INCLUDING PROPER TRANSPORTATION CLASSIFICATION AND PACKAGING. 3M's transportation classifications are based on product formulations, packaging, 3M policies and 3M's understanding of applicable current regulations and is valid for the original 3M package only. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and NOT THE PACKAGING, LABELING, OR MARKING REQUIREMENTS. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

For Transport Information, please visit [3M.com/Transportinfo](http://3M.com/Transportinfo)  
or call 1-800-364-3577 or 651-737-6501 for assistance.